


Tank Crosses - Short Cast NO LEAD Brass



General Tank Cross Features:

- Internal and external threads reduce fittings needed & installation time.
- Reduces turbulence and waterlogging in tanks without separate air chambers.
- **NO LEAD** brass tank crosses are **Third party certified to NSF/ANSI 372.**



NO LEAD BRASS Short cast crosses
Use with Flexcon Flex-Lite Series, WellMate Tanks



Part Number	Overall Length	Tank Conn.	Leg Conn.	Drain Ports Size (Qty)	Top Ports Size (Qty)	Material	USA or Import	Ctn Qty	List Price
CWM100BSNL	4 1/2"	1" (FIP)	1"x3/4"	1/2" (2)	1/4" (2)	NL Brass	Import	5/40	\$ 36.61
CWM125BSNL	4 3/4"	1 1/4" (FIP)	1 1/4"x1"	3/4" (2)	1/4" (2)	NL Brass	Import	4/32	48.93
CICS736BSNL	2 1/2"	1 1/4" MIP x 1" FIP	1"x3/4"	1/2" (2)	1/4" (2)	NL Brass	Import	5/40	39.29



NO LEAD BRASS Short cast female union tank crosses
Use with Flexcon "Flex-Lite" Series, WellMate Tanks.
FPT brass union w/ American Standard Buna-N o-ring.

- 1" uses AS 568-212 o-ring
- 1 1/4" uses AS 568-320 o-ring.



Part Number	Overall Length	Tank Conn.	Leg Conn.	Drain Ports Size (Qty)	Top Ports Size (Qty)	Material	USA or Import	Ctn Qty	List Price
CICS100BSFTUNL	4"	1" fpt union	1" x 3/4"	1/2" (2)	1/4" (2)	NL Brass	Import	4/32	\$ 45.89
CICS1251BSFTUNL	4"	1 1/4" fpt union	1" x 3/4"	1/2" (2)	1/4" (2)	NL Brass	Import	4/32	49.11
CICS125BSFTUNL	4"	1 1/4" fpt union	1 1/4" x 1"	3/4" (2)	1/4" (2)	NL Brass	Import	4/24	66.25



NO LEAD Short Cast Quick Connect (w/ Buna-N o-ring)
Crosses With alignment tabs for use with Well Mate
"Quick Connect" Series Tanks.

- 1" and 1 1/4" uses AS568-220 o-ring.



Part Number	Overall Length	Tank Conn.	Leg Conn.	Drain Ports Size (Qty)	Top Ports Size (Qty)	Material	USA or Import	Ctn Qty	List Price
CWM100BSQCNL	5"	Quick Connect	1" x 3/4"	1/2" (2)	1/4" (2)	NL Brass	Import	2/24	\$ 44.11
CWM125BSQCNL	5"	Quick Connect	1 1/4" x 1"	3/4" (2)	1/4" (2)	NL Brass	Import	2/24	58.75