

161T-LF Series

class 125, bronze disc, NPT swing check

lead free



job name:	
job location:	
engineer:	
contractor:	
tag:	
PO#:	
rep:	
wholesale dist.:	

description

The lead free* **Apollo® model 161T-LF (61YLF Series)** swing check provides a reliable, long lasting, “made in the USA” alternative to globally sourced check valves for potable water service. These valves are cast, machined, assembled, and tested in South Carolina using proven ASTM quality materials. The Apollo® swing check may be installed in either horizontal or vertical orientation with upward flow.

features

- lead free* ANSI 3rd party certified
- dezincification resistant bronze construction
- renewable bronze seat disc
- 100% factory tested per MSS SP-139
- NPT connection
- made in the USA
- Buy American Act (BAA) and BABA Act compliant

performance rating

- cold working pressure: 200 psi (13.8 bar) at 100°F
- saturated steam: 125 psi (8.6 bar) at 353°F
- temperature range: -20°F to 406°F

approvals

- MSS SP-80 design & tested
- MSS SP-139, “copper alloy gate, globe, & check valves”
- NSF/ANSI/CAN 372 lead free
- ASME B1.20.1, “pipe threads, general purpose (inch)”
- CSA B51 CRN OC14667.

precautionary note:
not recommended for applications which may induce pulsation or repetitive vibration. See Installation Manual for details.

standard material list

no.	component	material
1	body	ASTM B584-C89836 bronze
2	cap	ASTM B584-C89836 bronze
3	hanger	304 stainless steel or ASTM B584-C89836 bronze
4	pin	304 stainless steel
5	seat	C27451 lead free* DZR brass
6	plug	ASTM B16 brass

dimensions

part no.	size	weight	Cv(gpm)	dimensions	
				height	length
61YLF-193-01	1/2"	.73 lbs	7.0	1.65"	2.48"
61YLF-194-01	3/4"	1.1 lbs	12.0	1.90"	2.94"
61YLF-195-01	1"	1.7 lbs	28.6	2.26"	3.57"
61YLF-196-01	1-1/4"	3.4 lbs	39.0	2.99"	4.50"
61YLF-197-01	1-1/2"	3.1 lbs	56.0	2.99"	4.50"
61YLF-198-01	2"	5.5 lbs	152.0	3.74"	5.25"

warning: do not use in reciprocating compressor service.

*lead free: the wetted surfaces of this product shall contain no more than 0.25% lead by weighted average. Complies with Federal Public Law 111-380. ANSI 3rd party approved and listed.