

Large Volume Light Service Commercial Upright Electric Water Heater



Photo is of
SLE265T6

Bradford White Light Service Upright Electric Models Feature:

- **Fully Automatic Thermostat Controls**—Fast acting surface-mount thermostats with a high limit energy cut-off (manual reset) for safety.
- **Direct Heat Transfer With Immersed Elements**—Transfers heat directly and efficiently to the water. Screw-in style. INCOLOY® elements standard for all models.
- **Vitraglas® Lining with Microban®**—An exclusively engineered enamel formula that provides superior tank protection from the corrosive effects of water; and with Microban® antimicrobial product protection to help prevent the growth of bacteria, mold and mildew on the surface of the tank lining.
- **Factory-Installed Hydrojet® Total Performance System**—Sediment build-up reducing device that also increases first hour rating of hot water while minimizing temperature build-up in tank.
- **Insulation System**—2" (51mm) Non-CFC foam insulation covers the sides and top of the tank, reducing heat loss. This results in less energy consumption, improved efficiencies, and jacket rigidity.
- **Water Connections**—3/4" (19mm) NPT factory-installed true dielectric fittings extend water heater life and simplify water line connections. 1" (25mm) NPT for SLE2120T.
- **Factory-Installed Heat Traps**—Design incorporates a flexible disk that reduces heat loss in piping and eliminates the potential for noise generation.
- **Protective Anode Rod**—Provides added protection against corrosion for long-term, trouble-free service.
- **Steel Tank**—Heavy gauge steel automatically formed, rolled, and welded.
- **Wired at 277V, Single Phase, 12.2kW (6100W/6100W Simultaneous operation) only.**
- **T&P Relief Valve Installed On Top.**
- **NSF 5 kits available.**

FEATURING:



6-Year Limited Tank Warranties / 1-Year Limited Warranty on Component Parts.

For more information on warranty, please visit www.bradfordwhite.com
For products installed in USA and Puerto Rico. Some states do not allow limitations on warranties. See complete copy of the warranty included with the heater.

Microban® antimicrobial product protection helps prevent the growth of bacteria, mold and mildew that may affect the product. The built-in antimicrobial properties do not protect users or others from disease-causing organisms. Microban® is a registered trademark of Microban Products Company.

Commercial Electric Water Heater

Large Volume (Light Service) Upright Models

Meet or exceed ASHRAE 90.1 (latest edition). C.E.C. Listed



Model Number	Nominal Gal. Capacity		Recovery at 100°F Rise*		A Floor to Top of Heater	B Jacket Dia.	C Floor to Water Conn.	D C/L of Water Conn.	E Floor to T&P Conn.	G Water Conn. NPT	Approx. Shipping Weight
	U.S. Gal.	Imp. Gal.	U.S. GPH	Imp. GPH	in.	in.	in.	in.	in.	in.	lbs.
SLE265T6	65	54	50	42	60	22	61	8	61 ⁹ / ₁₆	3/4	156
SLE280T6	80	67	50	42	60	24	61	8	61 ⁹ / ₁₆	3/4	183
SLE2120T6	119	99	50	42	63	28	64 ¹³ / ₁₆	8	64 ⁹ / ₁₆	1	305
Model Number	Nominal Liter Capacity		Recovery at 56°C Rise*		A Floor to Top of Heater	B Jacket Dia.	C Floor to Water Conn.	D C/L of Water Conn.	E Floor to T&P Conn.	G Water Conn. NPT	Approx. Shipping Weight
			Liters/Hour		mm.	mm.	mm.	mm.	mm.	mm.	kg.
SLE265T6	246		189		1524	559	1549	203	1564	19	71
SLE280T6	303		189		1524	610	1549	203	1564	19	83
SLE2120T6	450		189		1600	711	1646	203	1640	25	138

* Based on 6100/6100, Simultaneous operation.

NSF 5 Kits available when ordering. All models meet DOE's standby loss requirements.

Wattage	Recovery ▲ GPH Temperature Rise °F					Wattage	Recovery ▲ LPH Temperature Rise °C				
	60	80	90	100	120		34	45	50	56	67
12,200W	82	62	56	50	42	12,200W	310	234	212	190	158

▲ GPH based on Simultaneous operation.



General:

All models are compliant with EPA Act. All heaters are wired inter-locking (Simultaneous, Single Phase) 277V with two 6100W elements. All water and electrical connections are 3/4" NPT (19mm) except for SLE2120T (1" NPT (25mm)). All models certified at 300 PSI test pressure (2068 kPa) and 150 PSI working pressure (1034 kPa.)

Dimensions and specifications subject to change without notice in accordance with our policy of continuous product improvement.

— BRADFORD WHITE IS —

**AMERICAN
STRONG**

Sales: 800-523-2931 ■ Fax 215-641-1612

24/7 Technical Support: 800-334-3393 ■ Email techserv@bradfordwhite.com

Products made by Bradford White are manufactured in the United States using the finest raw materials and components from around the world.

Built to be the Best®