

VITREOUS CHINA - COMMERCIAL ELONGATED/ADA 1.1 GPF FLUSH VALVE TOILET

Specifications;

684554 7501 Elongated Bowl

♿ 684556 7502 ADA Elongated Bowl

Features:

Made of Vitreous China

Elongated Rim (seat sold separately)

High Efficiency or Low Consumption

- Operates in the range of 1.1 gpf (4.2 Lpf) to 1.6 gpf (6 Lpf) depending on flushometer valve specified. (flushometer valve sold separately)
- 1.1 gpf (4.2 Lpf) systems operate at a 31% water savings when compared to Low Consumption toilet systems.

10" (254mm) or *12" (305mm) Rough In

Fully Glazed 2" (50mm) Trapway

11" (279mm) x 13" (330 mm) Water Surface Area

Direct Feed Jet

1 1/2" Inlet Spud (Included)

100% Factory Tested



Complies to the following Standards

ASME A112.19.2 / CSAB45.1

ICC/ANSI A117.1



7502 ADA Elongated Rim

Nominal Dimensions;

28-5/16" (719mm) long

15-7/16" (392mm) wide

17-1/8" (435mm) High

7501 Elongated Rim

Nominal Dimensions;

28-5/16" (719mm) long

15-7/16" (392mm) wide

14-3/8" (365mm) High

***Note:** This toilet is designed to rough-in at the standard dimension of 10" (254mm) and 12" (305mm) from the wall to the C/L of the outlet.

This drawing reflects a 10" (254mm) rough-in and additional calculations must be considered for a 12" (305mm) or any other dimensional rough-in.

