



Stainless Steel Connectors - Toilet / Dishwasher / Icemaker

Product Features

- Operating temperature: 25-150°F
- Burst pressure: 2000 PSI at 70°F
- Hose barbs: low lead brass (long length)
- Washers: Santoprene rubber
- Nuts: heavy duty nickel plated brass or plastic (acetal)
- Inner hose: Heavy duty reinforced PVC (1300 PSI burst pressure at 70°F)
- Operating pressure: 200 PSI
- A variety of lengths from 9" to 84"
- Outer wire braid: 304 stainless steel wire
- Ferrules: low lead brass

Installation Instructions

- For use with water in accessible locations only
- Hand tighten plus 1/4 turn. Plastic nuts are hand tighten only. Do not over tighten nuts.
- Check for leaks before leaving job site.
- Inspect regularly for general fitness and replace if damaged, corroded, or worn.
- Do not expose to corrosive chemicals.

Toilet Supply



Item No.	Description	Length	cUPC	IAPMO	ANSI/NSF 61	NSF372
586911	3/8" COMP X 7/8" BC	9"	•	•	•	•
586907	3/8" COMP X 7/8" BC	12"	•	•	•	•
586909	3/8" COMP X 7/8" BC	16"	•	•	•	•
586912	3/8" COMP X 7/8" BC	20"	•	•	•	•
586913	1/2" FIP X 7/8" BC	12"	•	•	•	•
586914	1/2" FIP X 7/8" BC	16"	•	•	•	•
586916	1/2" COMP X 7/8" BC	12"	•	•	•	•
586917	1/2" COMP X 7/8" BC	16"	•	•	•	•

Dishwasher Supply



Item No.	Description	Length	cUPC	IAPMO	ANSI/NSF 61	NSF372
586932	3/8" COMP X 1/2" FIP	60"	•	•	•	•
586929	3/8" COMP X 3/8" COMP	48"	•	•	•	•
586921	3/8" COMP X 3/8" COMP	60"	•	•	•	•
586925	3/8" COMP X 3/8" COMP	72"	•	•	•	•

Icemaker Supply



Item No.	Description	Length	cUPC	IAPMO	ANSI/NSF 61	NSF372
586935	1/4" COMP X 1/4" COMP	60"	•	•	•	•
586934	1/4" COMP X 1/4" COMP	72"	•	•	•	•
586940	1/4" COMP X 1/4" COMP	84"	•	•	•	•
586939	1/4" COMP X 1/4" COMP	96"	•	•	•	•
586936	1/4" COMP X 1/4" COMP	120"	•	•	•	•

Warranty and Codes

This product carries a 1-year limited warranty. ASME / IAPMO listed.

