

PRODUCT INFORMATION PACKET



Model No: B2982

Catalog No: B2982

Pool Pump Motor, 1.0/ .12 HP, 1 Ph, 60 Hz, 230 V, 3600 RPM, Y56Y Frame, ODP



Regal and Century are trademarks of Regal Rexnord Corporation or one of its affiliated companies.

©2022 Regal Rexnord Corporation, All Rights Reserved. MC017097E






Nameplate Specifications

Output HP	1.0/ .12 Hp	Output KW	0.75 kW
Frequency	60 Hz	Voltage	230 V
Current	SF 7.4/1.4 A	Speed	3450/1725 rpm
Service Factor	1.65	Phase	1
Duty	Continuous	Insulation Class	F
Frame	Y56Y	Enclosure	Open Drip Proof
Thermal Protection	Thermally Protected	Ambient Temperature	50 °C
UL	Recognized	CSA	Y


Technical Specifications

Electrical Type	Psc Low Speed, Cap Start/Cap Run High Speed	Poles	2/4
Rotation	Counterclockwise Pump End	Mounting	Square Flange
Motor Orientation	Horizontal	Drive End Bearing	BALL
Opp Drive End Bearing	BALL	Frame Material	Rolled Steel
Shaft Type	1/2 THREADS	Overall Length	13.40 in
Frame Length	9.00 in	Shaft Diameter	0.625 in
Shaft Extension	0.91 in		
Outline Drawing	B2982-S01	Connection Drawing	D0000026-001

This is an uncontrolled document once printed or downloaded and is subject to change without notice. Date Created:11/28/2022



REV	ECO	REV BY	DATE	APPD	DATE
D	0013035	VMS	03-18-2010	JOSUE	03-18-2010



(TWO SPEED)

GEOMETRIC CHARACTERISTICS & SYMBOLS
∟ FLATNESS
— STRAIGHTNESS
∠ ANGULARITY
⊥ PERPENDICULARITY (SQUARENESS)
// PARALLELISM
○ ROUNDNESS (CIRCULARITY)
⊘ CYLINDRICITY
△ PROFILE OF ANY SURFACE
⌒ PROFILE OF ANY LINE
↑ RUNOUT
⊕ TRUE POSITION
◎ CONCENTRICITY
≡ SYMMETRY

UNLESS OTHERWISE SPECIFIED
DIM. TOLERANCES ARE AS FOLLOWS:
INCH $\pm .1$ $\pm .02$ $\pm .005$ $\pm .0005$
mm ± 0.5 ± 0.13 ± 0.013
ANG. $\pm .50$ DEG
REMOVE BURRS & BREAK SHARP EDGES:
INCH .003-.015 mm 0.1-0.4
CORNER FILLETS TO:
INCH .020 mm 0.5
MACHINE SURFACES:
INCH $\sqrt{125}$ mm $\sqrt{3.2}$
METRIC DIMS. SHOWN IN [BRACKETS]



DR BY: Josue 07-15-2008
APPD: M. OVERHOLSER 07-15-2008
THIRD ANGLE PROJECTION
EDS DATE 02-22-2008
FORMAT REV F
CONFIDENTIAL: THIS DRAWING AND ITS INFORMATION ARE THE EXCLUSIVE AND CONFIDENTIAL PROPERTY OF A.O. SMITH CORP. AND ARE NOT TO BE DISCLOSED, DUPLICATED, DISTRIBUTED OR OTHERWISE USED WITHOUT THE WRITTEN CONSENT OF A.O. SMITH CORP.
-ALL RIGHTS RESERVED. ASME Y14.5M 1994



ELECTRICAL PRODUCTS COMPANY
A DIVISION OF A. O. SMITH CORPORATION

DESCRIPTION
CONN DIAGRAM - NAMEPLATE
SIZE A DWG NO D0000026-001
SCALE NONE SHEET 1

REVISION:	ECO	REVISADO POR:	FECHA:	APROBADO POR:	FECHA:
D	0013035	VMS	03-18-2010	JOSUE	03-18-2010



GRD


GREEN (GROUND)

USE COPPER
CONDUCTORS ONLY



INSTALL MOTOR
WITH VENTS DOWN

ACCEPTABLE FOR
FIELD WIRING

(DOS VELOCIDADES)

CARACTERISTICAS DE GEOMETRIA Y SIMBOLOS / PLANICIDAD — RECTITUD ∠ ANGULARIDAD ⊥ PERPENDICULARIDAD (A ESCUADRA) // PARALELISMO ○ REDONDEZ (CIRCULARIDAD) ⊘ CILINDRICIDAD ⌒ PERFIL DE CUALQUIER SUPERFICIE ⌒ PERFIL DE CUALQUIER LINEA ↑ VARIACION ⊕ POSICION REAL ◎ CONCENTRICIDAD ≡ SIMETRIA	A MENOS QUE SE ESPECIFIQUE DE OTRA MANERA, LAS TOLERANCIAS DE LAS DIMS. SON LAS SIGUIENTES: X XX XXX XXXX PULG ±.1 ±.02 ±.005 ±.0005 mm ±0.5 ±0.13 ±0.013 ANG. ±.50 GRADOS ELIMINAR REBABAS Y ORILLAS FILOSAS DEL BORDE. PULG .003-.015 mm 0.1-0.4 FILETEAR ESQUINA: PULG .020 mm 0.5 MAQUINAR SUPERFICIES PULG 125 mm 3.2 DIMS METRICAS MOSTRADAS [PARENTESIS]	DIBUJADO POR: Josue	07-15-2008	ELECTRICAL PRODUCTS COMPANY Innovation has a name. A DIVISION OF A. O. SMITH CORPORATION		
		APROBADO POR: M. OVERHOLSER	07-15-2008			
		TERCER ANGULO DE PROYECCION		FECHA EDS: 02-22-2008 REV. FORMATO: F	DESCRIPCION: CONN DIAGRAM – NAMEPLATE	
		CONFIDENCIAL: ESTE DIBUJO Y SU INFORMACION SON PROPIEDAD DE USO EXCLUSIVO Y CONFIDENCIAL DE A.O.SMITH CORP. Y NO DEBERAN SER REVELADOS, DUPLICADOS, DISTRIBUIDOS O USARSE DE OTRA MANERA SIN EL CONSENTIMIENTO ESCRITO DE A.O. SMITH CORP. –TODOS LOS DERECHOS RESERVADOS.ASME Y14.5M 1994			TAMAÑO: A	NUMERO DE DIBUJO: D0000026-001
					ESCALA:NONE	

版本	ECO	编制	日期	批准	日期
D	0013035	VMS	03-18-2010	JOSUE	03-18-2010



GRD



GREEN (GROUND)

USE COPPER
CONDUCTORS ONLY

INSTALL MOTOR
WITH VENTS DOWN

ACCEPTABLE FOR
FIELD WIRING

形位公差
□ 平面度
— 直线度
∠ 倾斜度
⊥ 垂直度
// 平行度
○ 圆度
⊙ 圆柱度
△ 面轮廓度
⌒ 线轮廓度
↗ 圆跳动
⊕ 位置度
◎ 同轴度
≡ 对称度

除另有注明
尺寸公差如下:
英寸 X XX XXX XXXX
毫米 ±.1 ±.02 ±.005 ±.0005
角度 ±.50 度
清理毛刺和尖棱
英寸 .003-.015 毫米 0.1-0.4
内圆角
英寸 .020 毫米 0.5
表面粗糙度
英制 125 米制 3.2
米制尺寸显示在[]

绘图:	Josue	07-15-2008
批准:	M. OVERHOLSER	07-15-2008
第三角投影		图纸格式发布日期 02-22-2008 图纸格式版本 F
机密: 本图纸及相关信息所有权归A. O. SMITH公司所有。 未经A. O. SMITH公司书面授权, 不得泄露、复制、传播或作 其他用途。一版权所有		
ASME Y14.5M 1994		

		ELECTRICAL PRODUCTS COMPANY A DIVISION OF A. O. SMITH CORPORATION	
名称 CONN DIAGRAM – NAMEPLATE			
图幅 A	图号 D0000026-001		
比例 NONE	页号 1		