

C						LOCATION										
	ADJUSTABLE FIXTURE SUPPORTS FOR SIPHON JET WATER CLOSETS SHALLOW ROUGH-IN TYPE															
	NO-HUB HORIZONTAL FITTINGS															
	SINGLE Fig. 0211RY Top View DOUBLE Fig. 0211DY Top View															
Front View																
NOTE: Base support and rear anchor must be securely anchored to floor (with four 1/2"(13) bolts provided by contractor). NOTE: Dimensions shown in parentheses are in millimeters.							The water closet gasket regularly furnished is made of molded neoprene and designed to fit water closet outlet dimensions and configurations shown in ANSI Standard A112.19.2M-1995, Figure 13B. If gasket is not found to be compatible to fixture due to nonconformance of said fixture to ANSI A112.19.2M, then fixture manufacturer shall be consulted for a suitable gasket recommendation. Jay R. Smith assumes no liability for connections to fixtures which do not conform to these standards.									
☐ Fig. 0211LY NO-HUB Left Hand ☐ Fig. 0211RY NO-HUB Right Hand ☐ Fig. 0211DY NO-HUB Double ☐ Fig. 0221LY NO-HUB Left Hand Long Barrel ☐ Fig. 0221RY NO-HUB Right Hand Long Barrel ☐ Fig. 0221DY NO-HUB Double Long Barrel <table border="1" style="width: 100%; border-collapse: collapse;"> <thead> <tr> <th rowspan="2">A SIZE</th> <th colspan="2">D</th> </tr> <tr> <th>MIN</th> <th>MAX</th> </tr> </thead> <tbody> <tr> <td>4 (100)</td> <td>5/8 (16)</td> <td>3 3/8 (86)</td> </tr> </tbody> </table>							A SIZE	D		MIN	MAX	4 (100)	5/8 (16)	3 3/8 (86)	Conforms with the requirements of ASME A112.6.1M up to a 500 lbs (227kg) static load rating.	
A SIZE	D															
	MIN	MAX														
4 (100)	5/8 (16)	3 3/8 (86)														
© dimension = 4" (100) (regularly furnished) consisting of nipple and Adjus-to-Wall coupling permitting adjustment from 3" (76) min. to 4" (100) max.							WEIGHT POUNDS VOLUME CUBIC FEET									
FIGURE NUMBER 0211Y, 0221Y																



WARNING: Cancer and Reproductive Harm - www.P65Warnings.ca.gov