

K	JAY R. SMITH MFG. CO.® MEMBER OF MORRIS GROUP INTERNATIONAL POST OFFICE BOX 3237 MONTGOMERY, ALABAMA 36109-0237 (USA) TEL: 334-277-8520 FAX: 334-272-7396 www.jrsmith.com LOCATION 																
	GENERAL PURPOSE ROOF DRAINS																
DRAWING NUMBER	ROOF DRAIN WITH ADJUSTABLE EXTENSION																
SIZE	FUNCTION: Used in flat roofs of any construction. The adjustable extension sleeve permits adjustment from a minimum of 1 1/4"(32) to a maximum of 4 "(100) easily accommodating up to 2 3/4"(70) of varying insulation thicknesses. The positive threading allows smooth perimeter movement and circumferential support of the top at any adjusted elevation. Large low profile dome provides sufficient free area for quick drainage of rainwater and protection against debris.																
SCALE:																	
DATE:	High Position 2 1/4 (57) MIN 4 (100) MAX Low Position 1 1/4 (32) MIN 2 1/2 (64) MAX 1 1/8 (29) MIN																
APPROVED BY:	Fig 1025S . . . SPIGOT OUTLET																
CHECKED BY:	NOTE: Dimensions shown in parentheses are in millimeters.																
DRAWN BY:	<table border="1" style="margin: auto; border-collapse: collapse;"> <tr> <td style="padding: 2px;">recommended deck opening</td> <td style="padding: 2px;">with suffix -R 17 (430) DIA</td> <td style="padding: 2px;">less suffix -R 14 (355) DIA</td> </tr> </table>					recommended deck opening	with suffix -R 17 (430) DIA	less suffix -R 14 (355) DIA									
recommended deck opening	with suffix -R 17 (430) DIA	less suffix -R 14 (355) DIA															
DIMENSIONS ARE SUBJECT TO MANUFACTURERS TOLERANCE AND CHANGE WITHOUT NOTICE	<table border="1" style="margin: auto; border-collapse: collapse;"> <tr> <td style="padding: 2px;">A SIZE</td> <td style="padding: 2px;">02(50)</td> <td style="padding: 2px;">03(75)</td> <td style="padding: 2px;">04(100)</td> <td style="padding: 2px;">05(125)</td> <td style="padding: 2px;">06(150)</td> </tr> <tr> <td style="padding: 2px;">B</td> <td style="padding: 2px;">5 1/2(140)</td> <td style="padding: 2px;">6(150)</td> <td style="padding: 2px;">6 1/4(160)</td> <td style="padding: 2px;">7(180)</td> <td style="padding: 2px;">7 1/2(190)</td> </tr> </table>					A SIZE	02(50)	03(75)	04(100)	05(125)	06(150)	B	5 1/2(140)	6(150)	6 1/4(160)	7(180)	7 1/2(190)
	A SIZE	02(50)	03(75)	04(100)	05(125)	06(150)											
B	5 1/2(140)	6(150)	6 1/4(160)	7(180)	7 1/2(190)												
REGULARLY FURNISHED: Duco Cast Iron Body with Side Outlet Elbow, Adjustable Extension Sleeve, Reversible Collar, Combined Flashing Clamp and Gravel Stop, with Polyethylene Dome. VARIATIONS: ☐ "L" Shaped Underdeck Clamp -CL ☐ Secondary Flashing Clamp -C2 ☐ Sump Receiver -R ☐ Underdeck Clamp -C ☐ Vandal Proof Dome -U OPTIONAL MATERIALS: ☐ ▲ Aluminum Dome -AD ☐ ▲ Cast Iron Dome -CID ☐ Galvanized Cast Iron Body and Collar -G ☐ ▲ Galvanized Cast Iron Dome -CIDG ☐ ▲ Rough Bronze Dome -RBD																	
FIGURE NUMBER	NOTE: Stated flow rates for roof drains are based on particular test piping configurations and dimensions. Installed roof drain flow rates cannot be stated unless the attached piping configuration is known and the effects of the drainage calculated.																
FIGURE NUMBER	▲ Optional domes' free area are as follows: <table style="margin: auto;"> <tr> <td>Aluminum</td> <td>98 (632)</td> </tr> <tr> <td>Cast Iron</td> <td>80 (516)</td> </tr> <tr> <td>Bronze</td> <td>95 (613)</td> </tr> </table>					Aluminum	98 (632)	Cast Iron	80 (516)	Bronze	95 (613)						
	Aluminum	98 (632)															
Cast Iron	80 (516)																
Bronze	95 (613)																
REV.	DATE	DESCRIPTION	BY	CKD. BY	FIGURE NUMBER 1025												



WARNING: Cancer and Reproductive Harm - www.P65Warnings.ca.gov