

FIGURE NUMBER 1330, 1340	DRAWN BY: TD	CHECKED BY: TD	APPROVED BY: TD	DATE: 5-24-85	SCALE: NONE	SIZE A	DRAWING NUMBER S1330	H																
	SMITH® JAY R. SMITH MFG. CO.® MEMBER OF MORRIS GROUP INTERNATIONAL POST OFFICE BOX 3237 MONTGOMERY, ALABAMA 36109-0237 (USA) TEL: 334-277-8520 FAX: 334-272-7396 www.jrsmith.com ASPE AMERICAN SOCIETY OF PROFESSIONAL ENGINEERS FPI FLAT PANEL INSTITUTE								LOCATION															
	GENERAL PURPOSE ROOF DRAINS																							
	8 1/2" (215) DIAMETER - LOW PROFILE DOME																							
	FUNCTION: Used in flat roofs, gutters or valleys of any construction. Small diameter pan is particularly adaptable to gutters and valleys where limited space is available. Flashing clamp holds flashing and roofing materials without puncturing. Low profile dome provides sufficient free area for quick drainage of rain water and protects the drain sump and connected piping from the intrusion of debris.																							
Free Area 41.5 SQ IN (268) SQ CM ☐ Fig. 1330C CAULK OUTLET ☐ Fig. 1330Y NO-HUB OUTLET ☐ Fig. 1340C CAULK OUTLET ☐ Fig. 1340T THREADED OUTLET A (Pipe Size) = 02(50), 03(75) or 04(100) <table border="1" style="margin-left: auto; margin-right: auto;"> <tr> <td colspan="2" style="text-align: center;">recommended deck opening</td> </tr> <tr> <td style="padding: 2px;">with suffix -R</td> <td style="padding: 2px;">9(230) DIA</td> </tr> <tr> <td style="padding: 2px;">less suffix -R</td> <td style="padding: 2px;">7 3/4(195) DIA</td> </tr> </table> *This Dimension to Internal Stop of Speedi-Set Gasket. ▲ Same for Caulk, NO-HUB and Speedi-Set, 4 1/4(110) for Threaded.									recommended deck opening		with suffix -R	9(230) DIA	less suffix -R	7 3/4(195) DIA										
recommended deck opening																								
with suffix -R	9(230) DIA																							
less suffix -R	7 3/4(195) DIA																							
REGULARLY FURNISHED: Duco Cast Iron Body with Combined Flashing Clamp and Gravel Stop with Polyethylene Dome. VARIATIONS: ☐ Expansion Joint (Specify Fig. 1710) (Fig. 1330 only) ☐ Extension -E (Specify Height) ☐ 2"(51) High Water Dam -WD ☐ "L" Shaped Underdeck Clamp -CL ☐ L Speedi-Set Service Weight (Fig. 1330 only) ☐ LXH Speedi-Set Extra Heavy (Fig. 1330 only) ☐ NO-HUB Adaptor (Specify Fig. 2646Y) (Fig. 1340 only) ☐ Secondary Flashing Clamp -C2 ☐ Sump Receiver -R ☐ Underdeck Clamp -C ☐ Vandal Proof Dome -U ☐ T Threaded Outlet OPTIONAL MATERIALS: ☐ Aluminum Dome -AD ☐ Cast Iron Dome -CID ☐ Galvanized Cast Iron Body & Collar -G ☐ Galvanized Cast Iron Dome -CIDG ☐ Rough Bronze Dome -RBD																								
NOTE: Stated flow rates for roof drains are based on particular test piping configurations and dimensions. Installed roof drain flow rates cannot be stated unless the attached piping configuration is known and the effects of the drainage calculated.																								
NOTE: Dimensions shown in parentheses are in millimeters.																								
<table border="1" style="width: 100%; border-collapse: collapse;"> <tr> <td style="width: 10%; text-align: center;">H G F E</td> <td style="width: 10%; text-align: center;">11-13-15 11-1-02 5-26-99 4-7-97</td> <td style="width: 30%; text-align: center;"> Added Flow Rate Note Rev. "V" Notch Rev. Opt. Mat. Added Millimeters </td> <td style="width: 10%; text-align: center;">TBW RN CMD EMB</td> <td style="width: 10%; text-align: center;">BW BS BS</td> <td style="width: 10%; text-align: center;">WEIGHT POUNDS</td> <td style="width: 10%; text-align: center;">VOLUME CUBIC FEET</td> <td style="width: 10%; text-align: center;"> FIGURE NUMBER 1330, 1340 </td> </tr> <tr> <td style="text-align: center;">REV.</td> <td style="text-align: center;">DATE</td> <td style="text-align: center;">DESCRIPTION</td> <td style="text-align: center;">BY</td> <td style="text-align: center;">CKD. BY</td> <td></td> <td></td> <td></td> </tr> </table>									H G F E	11-13-15 11-1-02 5-26-99 4-7-97	Added Flow Rate Note Rev. "V" Notch Rev. Opt. Mat. Added Millimeters	TBW RN CMD EMB	BW BS BS	WEIGHT POUNDS	VOLUME CUBIC FEET	FIGURE NUMBER 1330, 1340	REV.	DATE	DESCRIPTION	BY	CKD. BY			
H G F E	11-13-15 11-1-02 5-26-99 4-7-97	Added Flow Rate Note Rev. "V" Notch Rev. Opt. Mat. Added Millimeters	TBW RN CMD EMB	BW BS BS	WEIGHT POUNDS	VOLUME CUBIC FEET	FIGURE NUMBER 1330, 1340																	
REV.	DATE	DESCRIPTION	BY	CKD. BY																				



WARNING: Cancer and Reproductive Harm - www.P65Warnings.ca.gov