

E	SMITH® JAY R. SMITH MFG. CO.® MEMBER OF MORRIS GROUP INTERNATIONAL POST OFFICE BOX 3237 MONTGOMERY, ALABAMA 36109-0237 (USA) TEL: 334-277-8520 FAX: 334-272-7396 www.jrsmith.com ASPE AMERICAN SOCIETY OF PLUMBERS AND PIPEFITTERS MEMBER OF: PDI PLUMBING DRAINAGE INSTITUTE				LOCATION 		
	ADJUSTABLE FLOOR OR SHOWER DRAIN FLASHING STRAINER TYPE FUNCTION: Designed for clamping Altro Vinyl Traffic Flooring or other waterproofing materials at the finished floor level.						
DRAWING NUMBER							
SCALE: SIZE	FREE AREA 15 SQ IN (97) SQ CM 10 1/2 (265) DIA. 9 1/4 (235) DIA. 02 (50) MIN. 3 1/4 (83) MAX. 4 3/4 (120) A 5 1/2 (140) DIA. Flashing Clamp Vinyl Flooring Flashing Pan Collar Can Be Used as Flashing Device when Required						
DATE:	10-9-86						
APPROVED BY:	TD						
CHECKED BY:	CR						
DRAWN BY:	CMB						
FIGURE NUMBER	2050						
NOTE: Dimensions shown in parentheses are in Millimeters. NOTE: 2" (50) Inside Caulk Outlet only available by using 3" (75) inside Caulk Outlet with Caulk Reducer. A (Pipe Size) = 02(50), 03(75) or 04(100) Fig. 2050C.....Caulk Outlet Fig. 2050T.....Threaded Outlet REGULARLY FURNISHED: Duco Cast Iron Body with Flashing Collar and Nickel Bronze Adjustable Strainer.							
VARIATIONS: Trap Primer Connection - P050 Vandal Proof Screws - U No-Hub Adaptor (Specify Fig. 2646Y) OPTIONAL MATERIALS: Galvanized Body - G Polished Bronze - PB Chrome Plated Top - CP							
REV.	DATE	DESCRIPTION	BY	CKD. BY	WEIGHT POUNDS	VOLUME CUBIC FEET	FIGURE NUMBER
EDC	4-7-08 9-25-92 10/9/86	Revised Rev Pipe Sizes Revised & Redrawn	TBW EMB CMB	CL BS			2050



WARNING: Cancer and Reproductive Harm - www.P65Warnings.ca.gov