

F	DRAWING NUMBER S2310	SIZE A	SCALE: NONE	DATE: 5-17-85	APPROVED BY: TD	CHECKED BY: TD	DRAWN BY: PJ	2310, 2315	DIMENSIONS ARE SUBJECT TO MANUFACTURERS TOLERANCE AND CHANGE WITHOUT NOTICE	WE CAN ASSUME NO RESPONSIBILITY FOR USE OF SUPERSEDED OR VOID DATA	SMITH® JAY R. SMITH MFG. CO.® MEMBER OF MORRIS GROUP INTERNATIONAL POST OFFICE BOX 3237 MONTGOMERY, ALABAMA 36109-0237 (USA) TEL: 334-277-8520 FAX: 334-272-7396 www.jrsmith.com CUSTOMER DRIVEN SINCE 1926 ASPE MEMBER OF: American Society of Professional Engineers	LOCATION																			
											FLOOR DRAINS																				
											MEDIUM DUTY DRAINS WITH 8 1/2" ROUND ADJUSTABLE TOPS																				
											FUNCTION: Used in moderate traffic areas in any type of floor construction. Adjustable top collar permits accurate positioning of grate to meet finished floor level. Free Area 14.25 SQ IN (92) SQ CM Adjustable Top Seepage Openings Collar Can Be Used As Flashing Clamp (When Required) 12 (305) DIA 8 1/2 (215) DIA 8 (205) DIA ▲ 3 3/8 (86) MIN 4 5/8 (117) MAX 2 (51) B *2 1/2 (64) A 12 (305) DIA 8 1/2 (215) DIA 8 (205) DIA 3 3/8 (86) MIN^Δ 4 5/8 (117) MAX 2 (51) B A 6 (150) 4 (100) 5 1/2 (140) Fig. 2310C ... CAULK OUTLET Fig. 2310Y ... NO-HUB OUTLET Fig. 2315C ... CAULK OUTLET Fig. 2315T ... THREADED OUTLET <table><tr><td>A SIZE</td><td>02 (50)</td><td>03 (80)</td><td>04 (100)</td><td>06 (150)</td></tr><tr><td>B</td><td colspan="2">3 3/4 (95) for Caulk, NO-HUB, and Speedi-Set, 2 (51) for Threaded</td><td colspan="2">3 3/4 (95) NO-HUB Only</td></tr></table> *This Dimension to Internal Stop of Speedi-Set Gasket. ▲ add 3/16" (5) when bronze top is specified REGULARLY FURNISHED: Duco Cast Iron Body and Flashing Collar with Adjustable Top and Bar Grate. *Not available on Fig. 2310T threaded outlet drain VARIATIONS: ☐ Closure Plug -XP (Fig. 2310 only) ☐ Dome Grate -D ☐ Extensions (Specify Height) -E ☐ Flat Bottom Strainer -FBS (Fig. 2310 only) ☐ Hinged Grate -H ☐ L Speedi-Set Service Weight (Fig. 2310 only) ☐ LXH Speedi-Set Extra Heavy (Fig. 2310 only) ☐ NO-HUB Adaptor (Specify Fig. 2646Y) (Fig. 2315 only) ☐ Square Top -S ☒ Trap Primer Connection -P050 1/2"(13) & -P075 3/4"(19) ☐ Vandal Proof Grate -U ☐ T Threaded Outlet ☐ Quad Close Trap Seal (Specify Fig. 2692) (Fig. 2310 Only) OPTIONAL MATERIALS: ☐ Ductile Iron Grate -M ☐ Galvanized Cast Iron -G ☐ Nickel Bronze Top -NB ☐ Polished Bronze Top -PB ☐ Stainless Steel (Specify Fig. 9725) NOTE: Dimensions shown in parentheses are in millimeters.											A SIZE	02 (50)	03 (80)	04 (100)	06 (150)	B	3 3/4 (95) for Caulk, NO-HUB, and Speedi-Set, 2 (51) for Threaded		3 3/4 (95) NO-HUB Only	
											A SIZE	02 (50)	03 (80)	04 (100)	06 (150)																
B	3 3/4 (95) for Caulk, NO-HUB, and Speedi-Set, 2 (51) for Threaded		3 3/4 (95) NO-HUB Only																												
FIGURE NUMBER	F E D	6-18-15 11/17/05 12-11-97	Revised Variations Revised 2310 A-Size Table Revised Var & added note	TBW JJ EMB	CL CL DG	WEIGHT POUNDS	VOLUME CUBIC FEET	FIGURE NUMBER 2310, 2315																							
REV.	DATE		DESCRIPTION	BY	CKD. BY																										