

J	JAY R. SMITH MFG. CO. MEMBER OF MORRIS GROUP INTERNATIONAL POST OFFICE BOX 3237 MONTGOMERY, ALABAMA 36109-0237 (USA) TEL: 334-277-8520 FAX: 334-272-7396 www.jrsmith.com MEMBER OF: MEMBER OF:				LOCATION																
	FLOOR DRAINS WITH 8 1/2" ROUND ADJUSTABLE TOPS																				
DRAWING NUMBER	MEDIUM DUTY DRAINS WITH TRACTOR GRATE AND ADJUSTABLE TOP																				
SIZE	FUNCTION: Used in moderate traffic areas where waste water contains no sediment or debris and floor construction requires shallow drain body. Body flange and flashing collar serve as anchor in on grade locations and as flashing clamp when installed in waterproof floors. Adjustable top collar permits accurate positioning of grate to meet finished floor level.																				
SCALE:	Free Area 13 SQ IN (84) SQ CM																				
DATE:																					
APPROVED BY:	☐ Fig. 2320C . . . CAULK OUTLET ☐ Fig. 2320Y . . . NO-HUB OUTLET ☐ Fig. 2325C . . . CAULK OUTLET ☐ Fig. 2325T . . . THREADED OUTLET																				
CHECKED BY:	<table border="1" style="width: 100%; border-collapse: collapse; font-size: 8px;"> <tr> <th>A SIZE</th> <td>02 (50)</td> <td>03 (80)</td> <td>04 (100)</td> <td>06 (150)</td> </tr> <tr> <th>B</th> <td colspan="2">3 3/4 (95) for Caulk, NO-HUB, and Speedi-Set, 2 (51) for Threaded</td> <td colspan="2">3 3/4 (95) NO-HUB Only</td> </tr> </table>					A SIZE	02 (50)	03 (80)	04 (100)	06 (150)	B	3 3/4 (95) for Caulk, NO-HUB, and Speedi-Set, 2 (51) for Threaded		3 3/4 (95) NO-HUB Only							
A SIZE	02 (50)	03 (80)	04 (100)	06 (150)																	
B	3 3/4 (95) for Caulk, NO-HUB, and Speedi-Set, 2 (51) for Threaded		3 3/4 (95) NO-HUB Only																		
DRAWN BY:	<table border="1" style="width: 100%; border-collapse: collapse; font-size: 8px;"> <tr> <th>A SIZE</th> <td>02 (50)</td> <td>03 (75)</td> <td>04 (100)</td> </tr> <tr> <th>B</th> <td>4 1/4 (110)</td> <td>3 3/4 (95)</td> <td>3 1/4 (83)</td> </tr> </table>					A SIZE	02 (50)	03 (75)	04 (100)	B	4 1/4 (110)	3 3/4 (95)	3 1/4 (83)								
A SIZE	02 (50)	03 (75)	04 (100)																		
B	4 1/4 (110)	3 3/4 (95)	3 1/4 (83)																		
FIGURE NUMBER	REGULARLY FURNISHED: Duco Cast Iron Body and Flashing Collar with Adjustable Top and Tractor Grate.																				
	VARIATIONS: ☐ Closure Plug -XP (Fig. 2320 only) ☐ Extension (Specify Height) -E ☐ Flat Bottom Strainer -FBS (Fig. 2320 only) ☐ L Speedi-Set Service Weight (Fig. 2320 only) ☐ LXH Speedi-Set Extra Heavy (Fig. 2320 only) ☐ NO-HUB Adaptor (Specify Fig. 2646Y) (Fig. 2325 only) ☐ Square Top -S ☒ Trap Primer Connection -P050 1/2"(13) & -P075 3/4"(19) ☐ Vandal Proof Grate -U ☐ T Threaded Outlet ☐ Bucket -B ☐ Quad Close Trap Seal (Specify Fig. 2692) (Fig. 2320 Only) OPTIONAL MATERIALS: ☐ Ductile Iron Grate -M ☐ Galvanized Cast Iron -G ☐ Nickel Bronze Top -NB ☐ Polished Bronze Top -PB																				
REV.	*This Dimension to Internal Stop of Speedi-Set Gasket. △ add 3/16"(5) when bronze top is specified																				
DATE	NOTE Dimensions shown in parentheses are in millimeters.																				
DESCRIPTION	<table border="1" style="width: 100%; border-collapse: collapse; font-size: 8px;"> <tr> <th>REV.</th> <th>DATE</th> <th>DESCRIPTION</th> <th>BY</th> <th>CKD. BY</th> <th>WEIGHT POUNDS</th> <th>VOLUME CUBIC FEET</th> <th>FIGURE NUMBER</th> </tr> <tr> <td> </td> <td> </td> <td> </td> <td> </td> <td> </td> <td> </td> <td> </td> <td> </td> </tr> </table>					REV.	DATE	DESCRIPTION	BY	CKD. BY	WEIGHT POUNDS	VOLUME CUBIC FEET	FIGURE NUMBER								
REV.	DATE	DESCRIPTION	BY	CKD. BY	WEIGHT POUNDS	VOLUME CUBIC FEET	FIGURE NUMBER														
BY	2320, 2325 FIGURE NUMBER 2320, 2325 FIGURE NUMBER																				



WARNING: Cancer and Reproductive Harm - www.P65Warnings.ca.gov