

G	SMITH® JAY R. SMITH MFG. CO.® MEMBER OF MORRIS GROUP INTERNATIONAL POST OFFICE BOX 3237 MONTGOMERY, ALABAMA 36109-0237 (USA) TEL: 334-277-8520 FAX: 334-272-7396 www.jrsmith.com	PDI INSTITUTE	ASPE	MEMBER OF: ASSE American Society of Sanitary Engineers	LOCATION																																				
FLOOR DRAINS WITH 12" (305) ROUND ADJUSTABLE TOPS																																									
MEDIUM DUTY DRAINS																																									
FUNCTION: Used in medium traffic areas where large top drain is required. Adjustable top collar permits accurate positioning of top grate to meet finished floor level.																																									
Adjustable Top Seepage Openings Collar Can Be Used As Flashing Clamp (When Required) Adjustable Top Seepage Openings Collar Can Be Used As Flashing Clamp (When Required) A (Pipe Size) = 02(50), 03(80), 04(100), 05(125) or 06(150) ☐ Fig. 2330C . . .DEEP BODY CAULK OUTLET ☐ Fig. 2330Y . . .DEEP BODY NO-HUB OUTLET ☐ Fig. 2331C . . .SHALLOW BODY CAULK OUTLET Free Area 28.5 SQ IN (184) SQ CM ☐ Fig. 2335C . . .CAULK OUTLET ☐ Fig. 2335T . . .THREADED OUTLET <table><tr><th rowspan="2">Figure</th><th colspan="3">B</th><th rowspan="2">C DIA</th></tr><tr><th>Caulk</th><th>Thread</th><th>NO-HUB</th></tr><tr><td>2330</td><td>5(125)</td><td>3 3/4(95)</td><td>5(125)</td><td>15 1/4(390)</td></tr><tr><td>2331</td><td>3 3/4(95)</td><td>3 3/4(95)</td><td>-</td><td>16(405)</td></tr></table> *This Dimension to Internal Stop of Speedi-Set Gasket. Δ Add 1/8"(3) when bronze top is specified. Δ Add 7/8"(22) when hinged grate is specified. REGULARLY FURNISHED: Duco Cast Iron Body and Flashing Collar with Adjustable Top and Bar Grate. VARIATIONS: ☐ Adjustable Extensions 4 1/2(115) to 6"(150) -E ☐ Dome Grate -D ☐ Flat Bottom Strainer -FBS ☐ Hinged Grate -H ☐ L Speedi-Set Service Weight 02(50), 03(80) & 04"(100) sizes only (Fig. 2330 only) ☐ LXH Speedi-Set Extra Heavy 02(50), 03(80) & 04"(100) sizes only (Fig. 2330 only) ☐ NO-HUB Adaptor (Specify Fig. 2646Y) (Fig. 2331-2335 only) ☐ Square Top -S ☐ Trap Primer Connection -P050 1/2"(13) & -P075 3/4"(19) (Fig. 2330 only) ☐ Vandal Proof Grate -U ☐ T Threaded Outlet ☐ Quad Close Trap Seal (Specify Fig. 2692) (Fig. 2330 & 2331 Only) OPTIONAL MATERIALS: ☐ Ductile Iron Grate -M ☐ Galvanized Cast Iron -G ☐ Nickel Bronze Top -NB ☐ Polished Bronze Top -PB NOTE: 02(50), 03(80), & 04"(100) sizes require a transition collar (as shown in above illustration) which fits between the body & collar. 05(125) & 06"(150) sizes do not require transition collar. NOTE: Dimensions shown in parentheses are in millimeters. <table><tr><td rowspan="2">FIGURE NUMBER</td><td rowspan="2">2330, 2331, 2335</td><td rowspan="2">G F E D</td><td>6-18-15 4-9-97 7-5-94 9-30-93</td><td>Revised Variations Added Millimeters Revised Submittal Update</td><td>TBW EMB CMB EMB</td><td>CL BS BS</td><td>WEIGHT POUNDS</td><td>VOLUME CUBIC FEET</td><td>FIGURE NUMBER</td></tr><tr><td>REV.</td><td>DATE</td><td>DESCRIPTION</td><td>BY</td><td>CKD. BY</td><td></td><td></td><td>2330, 2331, 2335</td></tr></table>						Figure	B			C DIA	Caulk	Thread	NO-HUB	2330	5(125)	3 3/4(95)	5(125)	15 1/4(390)	2331	3 3/4(95)	3 3/4(95)	-	16(405)	FIGURE NUMBER	2330, 2331, 2335	G F E D	6-18-15 4-9-97 7-5-94 9-30-93	Revised Variations Added Millimeters Revised Submittal Update	TBW EMB CMB EMB	CL BS BS	WEIGHT POUNDS	VOLUME CUBIC FEET	FIGURE NUMBER	REV.	DATE	DESCRIPTION	BY	CKD. BY			2330, 2331, 2335
Figure	B			C DIA																																					
	Caulk	Thread	NO-HUB																																						
2330	5(125)	3 3/4(95)	5(125)	15 1/4(390)																																					
2331	3 3/4(95)	3 3/4(95)	-	16(405)																																					
FIGURE NUMBER	2330, 2331, 2335	G F E D	6-18-15 4-9-97 7-5-94 9-30-93	Revised Variations Added Millimeters Revised Submittal Update	TBW EMB CMB EMB	CL BS BS	WEIGHT POUNDS	VOLUME CUBIC FEET	FIGURE NUMBER																																
			REV.	DATE	DESCRIPTION	BY	CKD. BY			2330, 2331, 2335																															