

G	SMITH® JAY R. SMITH MFG. CO.® MEMBER OF MORRIS GROUP INTERNATIONAL POST OFFICE BOX 3237 MONTGOMERY, ALABAMA 36109-0237 (USA) TEL: 334-277-8520 FAX: 888-377-7818 www.jrsmith.com MEMBER OF: MEMBER OF: MEMBER OF:				LOCATION 															
	FLOOR DRAINS DECONTAMINATION DRAINS																			
DRAWING NUMBER S9205	SIZE A	SCALE: NONE	DATE: 8-12-93	APPROVED BY:	WE CAN ASSUME NO RESPONSIBILITY FOR USE OF SUPERSEDED OR VOID DATA	FUNCTION: Used in areas where hazardous or otherwise contaminated waste is present. Consists of two individual drains. Slotted grate drain permits drainage of contaminated waste to a separate storage tank, while the adjacent drain connected to the sewer is covered by a solid ground joint plug, thus preventing contaminated waste from entering the sewer system. Switching the solid cover and grate will allow washed down decontaminated waste to be directed to the sewer without entering the contaminated waste storage tank. Free Area 10.30 SQ IN (66) SQ CM Seepage Openings Collar Can Be Used As Flashing Clamp (When Required) Fig. 9205C CAULK OUTLET Fig. 9205Y NO-HUB OUTLET <table border="1" style="width: 100%; border-collapse: collapse; font-size: 8px;"> <tr> <td style="width: 20%;">A SIZE</td> <td>02(50), 03(75) & 04(100)</td> </tr> <tr> <td>B</td> <td>3 3/4 (95) for Caulk, NO-HUB and Speedi-Set®. 2 (51) for Threaded</td> </tr> </table> NOTE: Dimensions shown in parentheses are in millimeters. Δ This dimension to Internal Stop of Speedi-Set® Gasket TYPICAL INSTALLATION Drains are located close to each other for ease of switching grate and plug.				A SIZE	02(50), 03(75) & 04(100)	B	3 3/4 (95) for Caulk, NO-HUB and Speedi-Set®. 2 (51) for Threaded							
A SIZE	02(50), 03(75) & 04(100)																			
B	3 3/4 (95) for Caulk, NO-HUB and Speedi-Set®. 2 (51) for Threaded																			
CHECKED BY:	DRAWN BY: TWK	REGULARLY FURNISHED: Two (2) Duco Cast Iron Bodies with Flashing Collar and Bronze Rim. Cast Iron Grate and Ground Joint Plug. VARIATIONS: ☐ Engraved in Rims "Sanitary" and "Contaminated" ☐ L Speedi-Set® Service Weight ☐ LXH Speedi-Set® Extra Heavy ☐ T Threaded Outlet OPTIONAL MATERIALS: ☐ Acid Resistant Coated -ARC ☐ Bronze Grate and Plug -RB ☐ Galvanized Cast Iron -G ☐ Ductile Iron Grate and Plug -M																		
FIGURE NUMBER 9205	DIMENSIONS ARE SUBJECT TO MANUFACTURERS TOLERANCE AND CHANGE WITHOUT NOTICE	<table border="1" style="width: 100%; border-collapse: collapse; font-size: 8px;"> <tr> <td style="width: 10%;">REV.</td> <td style="width: 15%;">DATE</td> <td style="width: 30%;">DESCRIPTION</td> <td style="width: 10%;">BY</td> <td style="width: 10%;">CKD. BY</td> <td style="width: 15%;">WEIGHT POUNDS</td> <td style="width: 15%;">VOLUME CUBIC FEET</td> <td style="width: 15%; text-align: center;"> FIGURE NUMBER 9205 </td> </tr> <tr> <td> </td> <td> </td> <td> </td> <td> </td> <td> </td> <td> </td> <td> </td> <td> </td> </tr> </table>				REV.	DATE	DESCRIPTION	BY	CKD. BY	WEIGHT POUNDS	VOLUME CUBIC FEET	FIGURE NUMBER 9205							
REV.	DATE	DESCRIPTION	BY	CKD. BY	WEIGHT POUNDS	VOLUME CUBIC FEET	FIGURE NUMBER 9205													



WARNING: Cancer and Reproductive Harm - www.P65Warnings.ca.gov