




see what Delta can do™

BAR & PREP SINK FAUCETS

■ Single Handle Deck Mount

STANDARD SPECIFICATIONS:


- Max. flow rate 1.5 gpm @ 60 psi, 5.7 L/min @ 414 kPa
- One or three hole mount (order RP103661 for optional escutcheon)
- Spout rotates 360°
- Ceramic disc cartridge.
- Polymer braided flexible supply hose with 3/8" compression fitting thread connection

WARRANTY


- Parts and Finish – Lifetime limited warranty; or for commercial purchasers, 10 years for multi-family residential (apartments and condominiums) and 5 years for all other commercial uses, in each case from the date the product is received by the original purchaser or their authorized representative (installation contractor, etc.).
- Please go to www.deltafaucet.com for the complete details of our limited warranty

COMPLIES WITH:

- ASME A112.18.1 / CSA B125.1
- ICC/ANSI A117.1



▲ Designate proper finish suffix



Delta Faucet Company reserves the right (1) to make changes in specifications and materials, and (2) to change or discontinue models, both without notice or obligation. Dimensions are for reference only. See current full-line price book or www.deltafaucet.com for finish options and product availability.

Delta Faucet Company

55 E. 111th Street, Carmel, IN 46280
350 South Edgeware Road, St. Thomas, ON N5P 4L1
© 2026 Delta Faucet Company