

01724



Foam Sealant

- Tack free in 10 minutes
- Fully cured in 12 hours
- Paintable
- R Value 4.7
- UL Listed
- Not a fire stop
- No CFC or HCFC

Expanding Foam. A ready-to-use, multi-purpose, polyurethane foam that is triple expanding when in contact with air.

FEATURES: The expanding action fills holes, cracks and gaps more completely than standard caulks. It has excellent insulating properties and superb adhesion to virtually all building materials.

DANGER! EXTREMELY FLAMMABLE AEROSOL. PRESSURISED CONTAINER: MAY BURST IF HEATED.

Causes skin and serious eye irritation. May cause an allergic irritation. Harmful if inhaled. May cause allergy or asthma symptoms or breathing difficulties if inhaled. May cause respiratory irritation.

Suspected of causing cancer. May cause damage to organs through prolonged or repeated exposure.

FIRST AID: IF INHALED: Remove person to fresh air and keep comfortable for breathing. Call a poison center or a doctor if you feel unwell. **IF ON SKIN:** Wash skin with plenty of water. Take off contaminated clothing. If skin irritation or rash occurs: Get medical advice/attention. **IF IN EYES:** Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention. **IF SWALLOWED:** Call a poison center or a doctor if you feel unwell. See safety data sheet for further details regarding safe use of this product.

KEEP OUT OF REACH OF CHILDREN. Contains: Diphenylmethanedisocyanate, Polyol and Butane/Propane.

DIRECTIONS:

1. Shake can before use.
2. Surfaces must be clean and free of grease and oil.
3. Can must be held **UPSIDE DOWN** during application.
4. Insert straw into void and depress the trigger. The use of protective gloves is highly recommended.
5. Fill void 50% full to allow for expansion.
6. Uncured foam can be cleaned with acetone or paint thinner.
7. Cured foam can be trimmed, sanded, painted or stained. Foam **MUST** be painted or covered if application is exposed to UV light.

CLASSIFIED

 R38267 - CAULKINGS AND SEALANTS
 SURFACE BURNING CHARACTERISTICS
 APPLIED TO INORGANIC
 REINFORCED CEMENT BOARD+
 FLAME SPREAD - 10
 SMOKE DEVELOPED: 20
 +Tested in two 12.7 mm (1/2 in.) wide
 diameter beads, 8 in OC covering 5.5 % of
 the exposed test sample area.

Contains: polymethylepoxypolyphenylisocyanate. Harmful by inhalation. Irritating to eyes, respiratory system and skin. May cause sensitization by inhalation and skin contact. Do not breathe spray. Wear suitable protective clothing, gloves, and eye/face protection. In case of insufficient ventilation, wear respiratory equipment. In case of accident or if you feel unwell, seek medical advice (show the label where possible). Use only in well ventilated area. Keep away from sources of ignition - no smoking. Keep out of reach of children. Pressurized container. Protect from sunlight and do not expose to temperatures exceeding 50°C. Do not pierce or burn after use. Do not spray on a naked flame or any incandescent material. Contains isocyanates. See information supplied by the manufacturer.







**STORE CAN UPRIGHT TO
 AVOID OBSTRUCTION OF
 THE VALVE**



6650 Sugarloaf Parkway
 Duluth, GA 30097
 678-542-3600
www.diversitech.com

Made in Turkey



20 oz.

