

Pro-Lube POE 32

Polyolester

Refrigeration Compression Oil

ISO Grade 32

**For use with HFC and other highly
flourinated, environmentally safe
refrigerants**

OEM-Approved*

WARNING! May be harmful if
swallowed and enters airways.
Causes mild skin and eye irritation.



1 U.S. Quart (0.946 Liters)

DESCRIPTION: Diversitech's series of premium polyolester lubricants is custom formulated for use in refrigeration compressors. This series contains no ozone depleting substance and is compatible with new HFC refrigerants as well as existing CFC and HCFC refrigerants. In addition, DiversiTech's polyolester is compatible with traditional mineral oil lubricants.

These polyolester lubricants were developed in conjunction with compressor and refrigerant manufactures on a worldwide basis. They are custom formulated and offer the following performance advantages:

- Compatible with CFC, HCFC and HFC refrigerants
- Formulated to provide maximum protection against compressor wear
- Superior oil/refrigerant miscibility provides excellent oil-return
- Stable to chlorinated refrigerants for successful retrofits
- Compatible with existing refrigeration oils

WARNING! May be harmful if swallowed and enters airways. Causes mild skin and eye irritation. Keep out of reach of children. Read label before use. Do not handle until all safety precautions have been read and understood. Do not breathe mist, vapours, or spray. Do not get in eyes, on skin, or on clothing. Wear protective gloves, clothing, eye protection, and face protection.

FIRST AID: IF SWALLOWED: If more than several ounces of material are swallowed, DO NOT induce vomiting. Give two 16 ounce glasses of water and get medical attention or call the nearest poison control center for advice. **IF ON SKIN:** Remove contaminated clothing. Flush exposed area with water and follow by washing with soap if available. If persistent irritation occurs, obtain medical attention. When using high pressure equipment, injection of product under the skin can occur. If high pressure injuries occur, the affected person should be sent immediately to a hospital. Do not wait for symptoms to develop. Obtain medical attention even in the absence of apparent wounds. **IF INHALED:** Evacuate to a safe area with plenty of fresh air. Allow the affected individual to rest in a well ventilated area. Seek medical aid if breathing does not return to normal within 15 minutes.

IF IN EYES: Flush eye with copious quantities of water. If persistent irritation occurs, obtain medical attention.

IN CASE OF FIRE: Use any extinguisher suitable for Class B fires, dry chemical, CO₂, water spray or firefighting foam. See Safety Data Sheet for further details regarding safe use of this product.

NON-WARRANTY: This product is provided "as is". Seller specifically disclaims any and all warranties, whether expressed, implied, statutory or otherwise and specifically disclaims all implied warranties including without limitation, any implied warranties of merchantability or fitness for a particular purpose or those arising by reason of custom or usage in the trade or by course of dealing.

MADE IN USA
DOC13618

***Made from OEM-Approved
feedstocks**

Packaged & Distributed by:
DiversiTech Corporation
6650 Sugarloaf Parkway
Duluth GA, 30097 **678.542.3600**

Manufactured By:
The Lubrizol Corporation
2300 James Savage Road
Midland, MI 48642

