

Product Specifications



3/4" x 22' Rubber Tape

Part number 822
Category number 5370
UPC 781002281207



Rubber Tape is used in conjunction with friction and vinyl tape for use around split bolt connections, terminal lugs and compression connectors up to 600 volts. It is also frequently used in insulating and waterproof applications and can easily conform to irregular shapes and surfaces, yielding a void free, electrically stable buildup. It is compatible with all extruded dielectric cable insulations.

Physical Characteristics

Type	Rubber Tape
Length (ft)	22'
Width (in)	3/4"
Thickness (in)	0.030"
Thickness (mil)	30 mil
Material	Rubber
Backing Material	Rubber
Color	Black

Performance Data

Elongation	5
Maximum Continuous Temperature	176°F
Special Features	
Self-Amalgamating, Conforms to Irregular Shapes and Surfaces, Good Electrical Properties, Weather Resistant, Individual Cello Wrapped	
Dielectric Strength (kV/mm)	20 kV/mm
Water Resistant	Yes

Packaging Details

Standard Qty	1
Master Qty	100
Price Per	1
Package Length	4.00
Package Width	4.00
Package Height	0.60
Package Weight	0.37

Certifications

RoHS Compliant	Yes
Industry Standards	UL Listed
Meets/Exceeds	
ASTM D-4388 Type I	