

1/2"-13 Drop-In Anchor

Part Number DA50
Category Number 4500
UPC 781002276104

Drop-In Anchors are manufactured with an internally threaded, all-steel exterior shell that features an expansion cone insert used to anchor into the concrete. They are intended to be used in concrete materials only and can be used with any head style screw. The screw can easily be removed, loosened, or re-tightened if needed. Common applications include, pipe hanging, overhead anchoring, hanging strut, sprinkler systems and removable anchoring points.



Physical Characteristics

Install Tool	AT50
Anchor Type	Drop In
Thread Type	UNC
Anchor Diameter	1/2"
Anchor Length	2"
Thread Length	3/4"
Thread Per Inch	13
Thread Pitch\Thread Per Inch	1/2"-13
Material	Carbon Steel
Finish	Zinc Plated

Packaging Details

Standard Qty	50
Master Qty	250
Price Per	100
Package Length	7.20
Package Width	3.40
Package Height	2.20
Net Weight	0.1124
Package Weight	5.62

Performance Data

Pre-Drill Size	5/8"
Minimum Embedment Depth	2"
Applications	Pipe Hanging, Overhead Anchoring, Hanging Strut, Sprinkler Systems and Removable Anchor Points
Special Features	Zinc Plated, Easy Bolt Installation/Removal, Lip for Flush Installation, Expansion Cone Insert
Cement Type	Various PSI

Certifications

RoHS Compliant	Yes
----------------	-----