

Product Specifications



3/16" Flip Toggle Anchor Kit w/ Pan Head Combo Drive Screws

Part number FTG316
Category number 4740
UPC 781002854524



The Flip Toggle Anchor is a single piece, nylon body anchor with a metal tilting head ideal for use in drywall, plaster and hollow wall concrete blocks. It's unique tilting mechanism ensures a trouble-free installation that yields twice the strength of a regular toggle bolt of the same bolt diameter.

Physical Characteristics

Anchor Type	Flip Toggle
Head Type	Pan
Screw Size	#10-24 x 2-1/2"
Anchor Diameter	3/16"
Thread Pitch/Thread Per Inch	#10-24
Number of Pieces	10

Packaging Details

Kit Contains	
(10) Flip Toggle Anchors, (10) #10-24 x 2-1/2" Pan Phillips/Slotted Machine Screw	
Standard Qty	1
Sleeve Qty	0
Master Qty	10
Price Per	1
Package Length	9.60
Package Width	3.50
Package Height	1.50
Net Weight	0.68
Package Weight	0.68

Performance Data

Tension Strength	
1/2" Drywall: 134lbs, 5/8" Drywall: 214lbs, Hollow Concrete Block: 830lbs	
Safe Tension Load	
1/2" Drywall: 67lbs, 5/8" Drywall: 107lbs, Hollow Concrete Block: 415lb	
Shear Strength	
1/2" Drywall: 212lbs, 5/8" Drywall: 376lbs, Hollow Concrete Block: 870lbs	
Grip Range	1/2" to 2-1/8"
Hole Diameter	1/2"
Applications	
Drywall Hollow Block Walls and Ceilings	
Special Features	
Twice as Strong as Toggle Bolt, Fast and Easy Installation, Suitable for Overhead Applications, One Strap Design, Only Requires 1/2" Hole, Used with Any Bolt Length up to 3-3/4"	

Certifications

RoHS Compliant	Yes
----------------	-----