

The ReliaGuard®

Commercial Gas Connector

The Dormont® ReliaGuard® is a moveable-grade gas connector specifically engineered for caster-mounted commercial cooking equipment. The ReliaGuard includes a gray PVC coating and rotational end fittings.

The fuel gas codes require the use of an ANSI Z21.69/CSA 6.16 moveable gas connector with all appliances that may or may not utilize casters and, under normal use, are moved on a regular basis for service, positioning or area cleanliness.



Rotation technology reduces stress on both ends of the hose

Stainless Steel Braid
Tight-weave braid prevents corrugations from stretching as equipment is moved

Stainless Steel Construction
Heavy-duty, flexible, corrugated 304 stainless steel tubing

PVC Coating

From the trusted Dormont brand, ReliaGuard is designed for use with moveable equipment for ease of cleaning and repair. The ReliaGuard is composed of a 304 stainless steel corrugated tube covered with a tight weave stainless steel braid. The outside, composed of a gray PVC coating, is flame-resistant and can withstand temperatures up to 350°F. The end fittings of the connector allow for a 360° rotation, dramatically reducing stress at both hose ends. The ReliaGuard gas connector is flexible, durable, and corrosion resistant, making it the perfect solution to every commercial kitchen's gas connection needs.



- Standard Snap™ quick disconnect fitting

Standard Snap™



SwivelGuard™

- Reduces stress on connector
- Increases kitchen aisle space by allowing the appliance to be positioned closer to the wall



Restraining Cable

- Prevents transmission of strain to connector



Dormont.com

Dormont®
A WATTS Brand

Moveable Commercial Equipment Kits

Indicates most commonly stocked item

KIT SOLUTIONS available in 3', 4', and 5' lengths	50 = 1/2" ID 75 = 3/4" ID 100 = 1" ID	BTU/hr Minimum Flow Capacity*						List Price
	PART NUMBER		ReliaGuard®	Standard Snap™ QUICK-DISCONNECT	SwivelGuard™ 1st SWIVEL	SwivelGuard™ 2nd SWIVEL	RESTRAINING CABLE	
Standard Kit The ReliaGuard® Standard Snap Quick Disconnect Restraining Cable Two 90° Street Elbows Full Port Gas Valve	RG5036	77K	✓	✓			✓	\$268.83
	RG5048	68K	✓	✓			✓	\$280.15
	RG5060	60K	✓	✓			✓	\$297.14
	RG7536	218K	✓	✓			✓	\$294.30
	RG7548	180K	✓	✓			✓	\$311.28
	RG7560	158K	✓	✓			✓	\$328.26
	RG10036	379K	✓	✓			✓	\$495.22
	RG10048	334K	✓	✓			✓	\$520.68
	RG10060	294K	✓	✓			✓	\$560.29
Single SwivelGuard™ Kit The ReliaGuard Standard Snap Quick Disconnect One SwivelGuard Swivel Restraining Cable One 90° Street Elbows Full Port Gas Valve	RG50S36	72K	✓	✓	✓		✓	\$387.68
	RG50S48	63K	✓	✓	✓		✓	\$407.50
	RG50S60	56K	✓	✓	✓		✓	\$424.47
	RG75S36	203K	✓	✓	✓		✓	\$413.15
	RG75S48	167K	✓	✓	✓		✓	\$430.14
	RG75S60	147K	✓	✓	✓		✓	\$444.28
	RG100S36	353K	✓	✓	✓		✓	\$639.53
	RG100S48	310K	✓	✓	✓		✓	\$665.01
	RG100S60	274K	✓	✓	✓		✓	\$721.61
Double SwivelGuard Kit The ReliaGuard Standard Snap Quick-Disconnect Two SwivelGuard Swivels Restraining Cable Full Port Gas Valve	RG502S36	69K	✓	✓	✓	✓	✓	\$469.75
	RG502S48	60K	✓	✓	✓	✓	✓	\$506.54
	RG502S60	54K	✓	✓	✓	✓	✓	\$517.85
	RG752S36	193K	✓	✓	✓	✓	✓	\$503.71
	RG752S48	160K	✓	✓	✓	✓	✓	\$523.51
	RG752S60	140K	✓	✓	✓	✓	✓	\$543.31
	RG1002S36	336K	✓	✓	✓	✓	✓	\$798.01
	RG1002S48	295K	✓	✓	✓	✓	✓	\$831.97
	RG1002S60	261K	✓	✓	✓	✓	✓	\$854.60

*BTU/hr Minimum Flow Capacity (0.64 Sp.Gr., 1000 BTU/ft³ Natural Gas at 0.5" wc pressure drop)



**FREE display with
1/2 or full pallet
purchase of
ReliaGuard®**

Effective May 9, 2022

All prices supersede previous issues, are temporary and subject to change without notice.

Dormont®

A WATTS Brand



USA: T: (800) 367-6668 • F: (724) 733-4808 • Dormont.com