



Vero Vanity basin # 0330480017

| < 485 mm > |



Vanity basin	Dimension	Weight	Order number
undercounter basin, with overflow, without tap platform, fixings for installation in wooden consoles included, 485 mm			
Colors			
00 White Alpin			
Variant			
☒	485 x 315 mm	8.200 kilogram	0330480017
Infobox			
Measurements of undercounter models represent interior measurements			
Sanitary ceramics with the special WonderGliss surface finish will remain clean and attractive-looking for a long time to come. When ordering WonderGliss please add a "1" as eleventh digit to the model number.			
Push-open waste for washbasins with overflow		0.400 kilogram	005052
Design Siphon		1.500 kilogram	005036
Recommended faucets			
Single lever basin mixer XL ceramic cartridge, projection 180 mm, normal spray, chrome, maximum temperature can be adjusted on installation, recommended operating pressure 3 - 5 bar, with pop-up waste set, flexible connection hoses 9,53 mm (3/8"),			A11040001
2-hole electronic basin mixer XL with built-in power supply electronic control via operating knob, temperature change simply by rotating visualized by color light change, locking function for ease of cleaning, flow rate 5,0 l/min (3 bar), maximum temperature and waterflow time can be set individually, Permanent waterflow for thermal disinfection activatable, hygienic flush adjustable, scalding protection, normal spray, aerator adjustable, projection 180 mm, recommended operating pressure 3 - 5 bar, without pop-up waste set, without volume control, includes: spout, electronic control unit, operating knob (cable length 1200 mm),			D11110008

2-hole electronic basin mixer XL with plug-in power supply electronic control via operating knob, temperature change simply by rotating visualized by color light change, locking function for ease of cleaning, flow rate 5,0 l/min (3 bar), maximum temperature and waterflow time can be set individually, Permanent waterflow for thermal disinfection activatable, hygienic flush adjustable, scalding protection, normal spray, aerator adjustable, projection 180 mm, recommended operating pressure 3 - 5 bar, without pop-up waste set, without volume control, includes: spout, electronic control unit, operating knob (cable length 1200 mm),	D11110007
2-hole basin mixer XL ceramic cartridge, flexible connection hoses 9,53 mm (3/8"), connection size DN15, normal spray, flow rate 5,0 l/min (3 bar), aerator adjustable, projection 180 mm, recommended operating pressure 3 - 5 bar, without pop-up waste set,	D11130002
2-hole basin mixer XL with turning handle ceramic cartridge, flexible connection hoses 9,53 mm (3/8"), connection size DN15, normal spray, flow rate 5,0 l/min (3 bar), aerator adjustable, projection 180 mm, recommended operating pressure 3 - 5 bar, without pop-up waste set,	D11130009

All drawings contain the necessary measurements which are subject to standard tolerances. They are stated in mm and are non-binding. Exact measurements, in particular for customised installation scenarios, can only be taken from the finished ceramic piece.