



HeatLink Group Inc.

Head Office:

4603E - 13th Street NE

Calgary, AB, Canada

T2E 6M3

Toll Free (Canada & USA): 1-800-661-5332

Fax (Canada): 1-866-450-1155

Fax (USA): 1-800-869-6098

International Phone: +1 (403) 250-3432

International Fax: +1 (403) 250-1155

General Inquiries: info@heatlink.com

Purchase Orders: purchaseorder@heatlink.com

Quotation Requests: quotes@heatlink.com

Item # 20328, 1" 300ft Blue PureLink® Plus UV Stabilized PEX-a Tubing

High molecular crosslinked polyethylene (PEX) with minimum bending radius of 6× the diameter at 68°F (20°C). Maximum operating temperature 180°F at 100 psi (82°C at 7 bar). Blue printing for identification of cold water lines. The PureLink® Plus PEX-a tubing may be used with fittings that are compliant with ASTM F1807/F1960/F2080/F2098/F2159 standards.



[Specifications](#) | [Standards](#)

Specifications

Bend Radius	6 in 153 mm
Length	300 ft
Pkg Qty	1
Skid Qty	11
Unit	coil

Standards

Standards

ASTM F1807
ASTM F1960
ASTMF2080
ASTMF2098
ASTMF2159