



HeatLink Group Inc.

Head Office:

4603E - 13th Street NE

Calgary, AB, Canada

T2E 6M3

Toll Free (Canada & USA): 1-800-661-5332

Fax (Canada): 1-866-450-1155

Fax (USA): 1-800-869-6098

International Phone: +1 (403) 250-3432

International Fax: +1 (403) 250-1155



General Inquiries: info@heatlink.com

Purchase Orders: purchaseorder@heatlink.com

Quotation Requests: quotes@heatlink.com

Item # 26822NL, 1" x 3/4" x 3/4" PEX No Lead Brass Tee

Solid no lead brass (C69300-ecobrass) 1" x 3/4" x 3/4" PEX insert reducing tees. SS press sleeves sold separately.



[Specifications](#) | [Dimensions](#) | [Technical Data](#) | [Listings](#) | [Codes](#) | [Standards](#) | [Installation](#) | [Related Documents](#)

Specifications

Size (run x run x branch)¹ 1" x 3/4" x 3/4" PEX

Length 1.16 in
29.5 mm

Length L1 1.34 in
34 mm

Height 1.16 in
29.5 mm

Weight 0.078 kg
0.172 lb

Pkg Qty 5

Carton Qty 100

Unit

ea.

Dimensions

A

0.81 in
20.5 mm

B

0.53 in
13.5 mm

C

0.53 in
13.5 mm

D

0.63 in
16.0 mm

E

0.47 in
12.0 mm

F

0.53 in
13.5 mm

G

0.63 in
16.0 mm

ID1

0.71 in
18.0 mm

ID2

0.53 in
13.5 mm

ID3

0.53 in
13.5 mm

Technical Data

Material

No Lead (Eco) Brass - C69300

Operating Temperature [Max]

82.2 °C
180 °F

Operating Pressure [Max]

6.9 bar
100 psi

Listings

Listings

cNSFus-pw

Codes

—

Codes

IAPMO UPC

Standards

—

Standards

ASTM F877
 ASTM F1807
 CSA B137.5
 NSF/ANSI 14
 NSF/ANSI 61
 NSF/ANSI 372

Installation

—

Installation

Installation must follow all of HeatLink's instructions and guidelines.

Related Documents

—

Related Documents

HeatLink Limited Plumbing Warranty

¹ **Note:** 1-1/2" and larger fittings may be ordered in less than package quantities; no surcharge.