



AT175A1008/U
75VA, foot mounted 120/208/240 Vac transformer

- Product Info
- Literature

Overview

Honeywell 75 VA general purpose transformers power 24 Vac circuits.

Features

- Color-coded lead wires for primary connections and screw terminals for secondary connections
- Includes fixed 1/4 inch (6mm) male quick-connects (AT175A models only) or color-coded lead wires for primary and secondary connections
- Meets Underwriters Laboratories Standard UL 1585
- Identified Class 2 not wet, Class 3 wett

Product Specifications

Dimensions (in.)	3 3/16 in. high x 2 3/8 in. wide x 3 5/8 deep
Dimensions (mm)	81 mm high x 60 mm wide x 92 mm deep
Temperature Range (F)	-20 F to +105 F
Temperature Range (C)	-29 C to +41 C
Includes	Metal end bells
Mounting	Foot mounted, plate mounted on 2x4 in. or 4x4 in. outlet box , clamp mounted using outlet box knockout, or panel mounted
Electrical Ratings	Primary voltage--120 Vac, 208 Vac, 240 Vac; Secondary voltage--27.5 V.O.C.
Frequency	60 Hz
Approvals, Underwriters Laboratories Inc.	UL Listed: A,C,F models. File # E14881
Approvals, CSA	CSA Certified: A & B models.
Electrical Connections (Primary)(in.)	9 in. leadwires
Electrical Connections (Primary)(mm)	229 mm leadwires
Electrical Connections (Secondary)(in.)	(2) screw terminals
Electrical Connections (Secondary)(mm)	(2) screw terminals
Electrical Ratings, Output	24 Vac at 75 VA

shop our product catalog

commercial products
industrial products
residential products

support & resources

contractor pro
literature on demand
feedback

training

terms & conditions | privacy statement | site map

choose region & language