

C7089R Wireless Outdoor Sensor



Senses outdoor temperature and humidity to display on RedLINK™ enabled thermostats and accessories.

- Powered by RedLINK™ reliability
- No interference with other wireless devices in the home
- Reliable performance in all climates
- Installs in minutes
- Up to 5 year battery life
- 2 month low battery warning
- Battery warning displayed on RedLINK™ enabled thermostats
- Includes 2 AA Lithium batteries and mounting hardware

Application: Outdoor Sensor

Dimensions, Approximate: (with mounting bracket) 5 in. high x 3 1/2 in. wide x 1 11/16 in. deep ((with mounting bracket) 127 mm high x 89 mm wide x 43 mm deep)

Color: Gray

Operating Humidity Range (% RH): 0 to 100% RH, condensing

Operating Temperature Range: -40 F to 140 F (-40 C to 60 C)

Power Method: Battery

Sensor Element: Thermistor

Mounting: Mounts on a vertical wall with supplied bracket and mounting hardware

Product Number	Comments	Used With	Includes
C7089R1013/U	Wireless Outdoor Sensor is also available in kits	RedLINK™ enabled thermostats and accessories	2 AA Lithium Batteries and mounting hardware

C7189R Wireless Indoor Air Sensor



The Wireless Indoor Sensor(s) is used to change the sensing location of the thermostat. Sense temperature and humidity remotely, average temperature, and humidify and dehumidify in separate locations.

- The Wireless Indoor Sensor(s) is used to change the sensing location of the thermostat.
- Sense temperature and humidity remotely.
- Average temperature
- Control temperature and humidity in separate locations.
- Humidify and dehumidify in separate locations. For example, humidify on the main level and dehumidify in the crawl space.
- Up to 6 Wireless Indoor Sensors per thermostat.

Application: Wireless Indoor Air Sensor

Dimensions, Approximate: 2 7/8 in. high x 1 7/8 in. wide x 15/16 in. deep (73 mm x 48 mm x 24 mm)

Color: Arctic White

Operating Humidity Range (% RH): 5 to 90% RH, non-condensing

Operating Temperature Range: 0 F to 120 F (-17.8 C to 48.9 C) (35 F to 114 F (1.7 C to 45.6 C) for optimal battery life)

Power Method: Battery

Mounting: Mounts on a vertical wall with supplied bracket and mounting hardware

Product Number	Description	Used With	Includes
C7189R1004/U	Senses indoor temperature and humidity	Prestige® IAQ, Prestige® 2.0 and VisionPRO with RedLINK™ Thermostats	2 AAA alkaline batteries and mounting hardware

REM1000 RedLINK™ Wireless Entry/Exit Remote



Application: Heating and Cooling systems, RedLINK Thermostat Accessory

Dimensions, Approximate : 6 1/4 in. high x 3 1/8 in. wide x 1 5/8 in. deep (159 mm high x 79 mm wide x 41 mm deep)

Used With: RedLINK™ enabled thermostats and accessories

Color: White

Operating Humidity Range (% RH): 5 to 90% RH, non-condensing
Operating Temperature Range : 35 F to 114 F (1.7 C to 45.6 C) for optimal battery life

Sensor Element: Thermistor

Power Method: Battery, Lithium Coin Cell

Accessories:

HVC20A1000-Wireless Vent and Filter Boost Remote

Product Number	Description
REM1000R1003/U	RedLINK Wireless Entry/Exit Remote