

MISCELLANEOUS PRODUCTS

85220
Pit Drain, Threaded Side Outlet



Page 258

85800
12-3/4" x 7-1/2" Top, Threaded Outlet



Page 258

85810
12-7/8" x 5-3/8" Top, Inside Caulk Outlet



Page 259

85903-Z
Light Traffic Drain, No-Hub Outlet



Page 259

P-TRAPS

88100
Spigot Connections



Page 260

88210
Funnel Inlet, Side Outlet
Threaded Connection



Page 260

TRAP SEAL PRIMERS

88250
Primer Valve, Vacuum Breaker,
Gasketed Cover



Page 261

88300
Trap Primer & Distribution Unit



Page 261

ADAPTERS

88400
No-Hub Spigot Adapter



Page 262

88450
Trap Primer Adapter



Page 262

88550
Hub Adapter, Female Threaded Outlet



Page 263

88560 **88600**
Hub Adapter Reducing Hub
Male Threaded Outlet



Pages 263, 264

AIR GAPS

88900
Threaded Inlet, XH Spigot Outlet



Page 264

88910
Female Threaded Inlet & Outlet



Page 265

FRESH AIR INLETS

88950
Perforated Grille



Page 265

88970
Convex Grille



Page 266

88250 SERIES TRAP SEAL PRIMER VALVE					
APPLICATION For use with tapped floor drains in locations where infrequent use or other conditions might permit the water seal to evaporate, allowing sewer gas or objectionable and contaminating odors to escape through the drain. The trap primer valve is connected to a water supply line and sends a precise amount of water, with each use, to the trap to compensate for evaporation and ensure maintenance of a water seal in the trap at all times. SPECIFICATION JOSAM 88250 Series all bronze Primer Valve with removable operating parts, integral vacuum breaker and gasketed access cover for installation in a cold water service line to a plumbing fixture with trap connection for maintaining trap seal.	<table border="1"> <thead> <tr> <th>TYPE NO.</th><th>LBS.</th></tr> </thead> <tbody> <tr> <td>88250</td><td>3</td></tr> </tbody> </table>	TYPE NO.	LBS.	88250	3
TYPE NO.	LBS.				
88250	3				
Available Options -10 Polished Chrome Plated -90 1/2" Female Copper Connection -91 1/2" Female IPS Union Connection					
88300 SERIES TRAP PRIMER VALVE & DISTRIBUTION UNIT					
APPLICATION For use with two to four tapped floor drains in locations where infrequent use or other conditions might permit the water seal to evaporate, allowing sewer gas or objectionable and contaminating odors to escape through the drain. The trap primer valve is connected to a cold water supply line and sends a precise amount of water, with each use, to the trap to compensate for evaporation and ensure maintenance of a water seal in the trap at all times. SPECIFICATION JOSAM 88300 Series all bronze trap primer valve with 1/2" N.P.T. inlet, integral back-flow preventer, vacuum breaker ports and 1/2" F.N.P.T. outlet for connection to plastic distribution unit for two to four plumbing fixtures.	<table border="1"> <thead> <tr> <th>TYPE NO.</th><th>LBS.</th></tr> </thead> <tbody> <tr> <td>88300</td><td>1.5</td></tr> </tbody> </table>	TYPE NO.	LBS.	88300	1.5
TYPE NO.	LBS.				
88300	1.5				