

A	JAY R. SMITH MFG. CO.® MEMBER OF MORRIS GROUP INTERNATIONAL POST OFFICE BOX 3237 MONTGOMERY, ALABAMA 36109-0237 (USA) TEL: 334-277-8520 FAX: 888-377-7818 www.jrsmith.com MEMBER OF: MEMBER OF: MEMBER OF:				LOCATION 			
	GENERAL PURPOSE ROOF DRAINS							
DRAWING NUMBER SDX1240	SIZE A	SCALE: NONE	DATE: 8-10-06	APPROVED BY: CL	CHECKED BY: CL	DRAWN BY: TBW	DIMENSIONS ARE SUBJECT TO MANUFACTURERS TOLERANCE AND CHANGE WITHOUT NOTICE	
MEDIUM WIDE FLANGE BODY WITH "SAFE-SET" BUCKET								
FUNCTION: Used in promenade roof decks where waterproof traffic bearing covering is to be applied. Sediment bucket prevents debris from entering the waste system.								
Free Area 9.25 SQ IN (60) SQ CM A (Pipe Size) = 02(50), 03(75) or 04(100) Fig. DX1240C CAULK OUTLET Fig. DX1240T THREADED OUTLET △ add 3/16"(5) when bronze top is specified.								
REGULARLY FURNISHED: Duco Cast Iron Wide Flange Body with ADA Slotted Grate and "Safe-Set" Sediment Bucket. Use only where light rainfall is prevalent or in covered roof areas. When heavy rainfall is anticipated use DX1010 or DX2566. NOTE: Recommended deck opening 9 1/4(235). VARIATIONS: ☐ Membrane Clamp (Specify DX2565R) ☐ NO-HUB Adaptor (Specify Fig. 2646Y) ☐ Securing Holes -SH ☐ Underdeck Clamp -C OPTIONAL MATERIALS: ☐ Galvanized Cast Iron -G ☐ Nickel Bronze Top -NB ☐ Polished Bronze Top -PB NOTE: Dimensions shown in parentheses are in millimeters.								
FIGURE NUMBER DX1240	REV. 	DATE 	DESCRIPTION 	BY 	CKD. BY 	WEIGHT POUNDS 	VOLUME CUBIC FEET 	FIGURE NUMBER DX1240



WARNING: Cancer and Reproductive Harm - www.P65Warnings.ca.gov