

B	SMITH® JAY R. SMITH MFG. CO.® MEMBER OF MORRIS GROUP INTERNATIONAL POST OFFICE BOX 3237 MONTGOMERY, ALABAMA 36109-0237 (USA) TEL: 334-277-8520 FAX: 888-377-7818 www.jrsmith.com MEMBER OF: MEMBER OF: MEMBER OF:					LOCATION		
	GENERAL PURPOSE ROOF DRAINS							
DRAWING NUMBER SDX1250	SIZE A	SCALE: NONE	DATE: 8-10-06	APPROVED BY: CL	CHECKED BY: CL	DRAWN BY: TBW	DIMENSIONS ARE SUBJECT TO MANUFACTURERS TOLERANCE AND CHANGE WITHOUT NOTICE	
SQUARE WIDE FLANGE BODY WITH NICKEL BRONZE TRACTOR GRATE FUNCTION: Used in either wood or concrete deck installation where waterproof finished decks are installed. Large flange provides ample surface to receive the waterproofing membranes and the finished topping coat. Free Area 12.5 SQ IN (81) SQ CM A (Pipe Size) = 02(50), 03(75) or 04(100) Fig. DX1250C CAULK OUTLET Fig. DX1250T THREADED OUTLET REGULARLY FURNISHED: Duco Cast Iron Wide Flange Body with Nickel Bronze ADA Tractor Grate and Rim. Use only where light rainfall is prevalent or in covered roofareas. When heavy rainfall is anticipated, use DX1010 or DX2566. VARIATIONS: ☐ Membrane Clamp (Specify DX2565R) ☐ NO-HUB Adaptor (Specify Fig. 2646Y) ☐ Sediment Bucket -B ☐ Underdeck Clamp -C OPTIONAL MATERIALS: ☐ Galvanized Cast Iron -G ☐ Polished Bronze -PB NOTE: Recommended deck opening 9 1/4(235). NOTE: Dimensions shown in parentheses are in millimeters.								
FIGURE NUMBER DX1250	B A	1-19-23 7-20-22	Added ADA to Reg. Furnished Revised Variations	KK KK	CL CL	WEIGHT POUNDS	VOLUME CUBIC FEET	FIGURE NUMBER DX1250
REV.	DATE	DESCRIPTION		BY	CKD. BY			



WARNING: Cancer and Reproductive Harm - www.P65Warnings.ca.gov