

L	SMITH® JAY R. SMITH MFG. CO.® MEMBER OF MORRIS GROUP INTERNATIONAL POST OFFICE BOX 3237 MONTGOMERY, ALABAMA 36109-0237 (USA) TEL: 334-277-8520 FAX: 334-272-7396 www.jrsmith.com MEMBER OF: MEMBER OF:				LOCATION
	PROMENADE DECK DRAIN FOR INSULATED ROOF DECKS				
DRAWING NUMBER	S1459				
SIZE	A				
SCALE:	NONE				
DATE:	2-2-82				
APPROVED BY:	JM				
CHECKED BY:	JM				
DRAWN BY:	KG				
FIGURE NUMBER	1459				

WE CAN ASSUME NO RESPONSIBILITY FOR USE OF SUPERSEDED OR VOID DATA

DIMENSIONS ARE SUBJECT TO MANUFACTURERS TOLERANCE AND CHANGE WITHOUT NOTICE

Fig. 1459C CAULK OUTLET

Fig. 1459Y NO-HUB OUTLET

REGULARLY FURNISHED:
 Duco Cast Iron Body and 4" (100) Extension with Secondary Flashing Clamp and Seepage Openings with Secured Square Hole Grate.

* On some systems this layer includes a layer of pea gravel and a layer of insulation.

VARIATIONS:

Expansion Joint (Specify Fig. 1710)
 Extension (Specify Height) -E
 "L" Shaped Underdeck Clamp -CL
 L Speedi-Set Service Weight
 02(50), 03(75) & 04"(100) sizes only
 LXH Speedi-Set Extra Heavy
 02(50), 03(75) & 04"(100) sizes only
 NO-HUB Adaptor (Specify Fig. 2646Y)
 Sump Receiver -R
 Underdeck Clamp -C
 Vandal Proof Grate -U
 T Threaded Outlet
 S.S. Perforated Extension

OPTIONAL MATERIALS:

Ductile Iron Grate -M
 Galvanized Cast Iron -G
 Nickel Bronze Top -NB
 Polished Bronze Top -PB

recommended deck opening

with suffix -R	13 (330) DIA
less suffix -R	11 (280) DIA

NOTE: Dimensions shown in parentheses are in millimeters.

REV.	DATE	DESCRIPTION	BY	CKD. BY	WEIGHT POUNDS	VOLUME CUBIC FEET	FIGURE NUMBER 1459

WARNING: Cancer and Reproductive Harm - www.P65Warnings.ca.gov