

G	JAY R. SMITH MFG. CO.® MEMBER OF MORRIS GROUP INTERNATIONAL POST OFFICE BOX 3237 MONTGOMERY, ALABAMA 36109-0237 (USA) TEL: 334-277-8520 FAX: 334-272-7396 www.jrsmith.com MEMBER OF: MEMBER OF:				LOCATION 																																																														
	FLOOR OR SHOWER DRAIN																																																																		
DRAWING NUMBER																																																																			
SIZE	A																																																																		
SCALE:	NONE																																																																		
DATE:	1-22-76																																																																		
APPROVED BY:	WZ																																																																		
CHECKED BY:	WZ																																																																		
DRAWN BY:	WH																																																																		
2009	•Add 3/8"(10) to all min./max. dimensions for round strainers. *Collar is reversible to obtain extreme high and low strainer positions. Caulk Regular Fig. 2009C . . . (A) ROUND TOP Fig. 2009C . . . (B) SQUARE TOP Deck Opening 11 1/4 (285) MIN <table border="1" style="width: 100%; border-collapse: collapse; font-size: 10px;"> <thead> <tr> <th rowspan="2">Strainer Size</th> <th colspan="2">* Collar In High Position</th> <th colspan="2">* Collar In Low Position</th> <th colspan="2">Free Area SQ IN</th> </tr> <tr> <th colspan="2">X</th> <th colspan="2">XX</th> <th>Round</th> <th>Square</th> </tr> <tr> <th>B Dia. or Sq.</th> <th>Min</th> <th>Max</th> <th>Min</th> <th>Max</th> <th></th> <th></th> </tr> </thead> <tbody> <tr> <td>05 (125)</td> <td>1 1/4 (32)</td> <td>2 1/4 (57)</td> <td>3/4 (19)</td> <td>1 5/8 (41)</td> <td>7 (45)</td> <td>6.5 (42)</td> </tr> <tr> <td>06 (150)</td> <td>1 1/4 (32)</td> <td>2 1/4 (57)</td> <td>3/4 (19)</td> <td>1 5/8 (41)</td> <td>9 (58)</td> <td>12.5 (81)</td> </tr> <tr> <td>07 (180)</td> <td>1 1/4 (32)</td> <td>2 1/4 (57)</td> <td>7/8 (22)</td> <td>1 7/8 (48)</td> <td>14 (90)</td> <td>11 (71)</td> </tr> <tr> <td>08 (205)</td> <td>1 1/2 (38)</td> <td>2 1/2 (64)</td> <td>1 (25)</td> <td>1 7/8 (48)</td> <td>18 (116)</td> <td>14 (90)</td> </tr> <tr> <td>•09 (230)</td> <td>1 1/2 (38)</td> <td>2 3/8 (60)</td> <td>1 (25)</td> <td>1 7/8 (48)</td> <td>19 (123)</td> <td>16 (103)</td> </tr> <tr> <td>•10 (255)</td> <td>1 1/2 (38)</td> <td>2 3/8 (60)</td> <td>1 (25)</td> <td>1 7/8 (48)</td> <td>23 (148)</td> <td>16 (103)</td> </tr> </tbody> </table>					Strainer Size	* Collar In High Position		* Collar In Low Position		Free Area SQ IN		X		XX		Round	Square	B Dia. or Sq.	Min	Max	Min	Max			05 (125)	1 1/4 (32)	2 1/4 (57)	3/4 (19)	1 5/8 (41)	7 (45)	6.5 (42)	06 (150)	1 1/4 (32)	2 1/4 (57)	3/4 (19)	1 5/8 (41)	9 (58)	12.5 (81)	07 (180)	1 1/4 (32)	2 1/4 (57)	7/8 (22)	1 7/8 (48)	14 (90)	11 (71)	08 (205)	1 1/2 (38)	2 1/2 (64)	1 (25)	1 7/8 (48)	18 (116)	14 (90)	•09 (230)	1 1/2 (38)	2 3/8 (60)	1 (25)	1 7/8 (48)	19 (123)	16 (103)	•10 (255)	1 1/2 (38)	2 3/8 (60)	1 (25)	1 7/8 (48)	23 (148)	16 (103)
	Strainer Size	* Collar In High Position		* Collar In Low Position			Free Area SQ IN																																																												
X		XX		Round	Square																																																														
B Dia. or Sq.	Min	Max	Min	Max																																																															
05 (125)	1 1/4 (32)	2 1/4 (57)	3/4 (19)	1 5/8 (41)	7 (45)	6.5 (42)																																																													
06 (150)	1 1/4 (32)	2 1/4 (57)	3/4 (19)	1 5/8 (41)	9 (58)	12.5 (81)																																																													
07 (180)	1 1/4 (32)	2 1/4 (57)	7/8 (22)	1 7/8 (48)	14 (90)	11 (71)																																																													
08 (205)	1 1/2 (38)	2 1/2 (64)	1 (25)	1 7/8 (48)	18 (116)	14 (90)																																																													
•09 (230)	1 1/2 (38)	2 3/8 (60)	1 (25)	1 7/8 (48)	19 (123)	16 (103)																																																													
•10 (255)	1 1/2 (38)	2 3/8 (60)	1 (25)	1 7/8 (48)	23 (148)	16 (103)																																																													
REGULARLY FURNISHED: Duco Cast Iron Body with Wide Flange, Cast Iron Flashing Collar, Adjustable Strainer Head as Indicated by Suffix Letter Selected and Secured Square Hole Grate. NOTE: Dimensions shown in parentheses are in millimeters VARIATIONS: Backwater Valve -V Sediment Bucket -B Trap Primer Conn. -P50 1 1/2"(13) & -P75 3/4"(19) Vandal Proof Screws -U Y NO-HUB Outlet T Threaded Outlet Quad Close Trap Seal (Specify Fig. 2692) OPTIONAL MATERIALS: Bronze Body -G Chrome Plated Bronze Strainer Head -CP Galvanized Body -G Nickel Bronze -NB Polished Bronze Strainer Head -PB Stainless Steel Strainers -SS [Available in 05(125) & 06(150) sizes only]																																																																			
FIGURE NUMBER	2009																																																																		
REV.	DATE	DESCRIPTION	BY	CKD. BY	WEIGHT POUNDS VOLUME CUBIC FEET FIGURE NUMBER 2009																																																														