

F	SMITH® JAY R. SMITH MFG. CO.® MEMBER OF MORRIS GROUP INTERNATIONAL POST OFFICE BOX 3237 MONTGOMERY, ALABAMA 36109-0237 (USA) TEL: 334-277-8520 FAX: 334-272-7396 www.jrsmith.com MEMBER OF:				LOCATION 																																																											
	FLOOR DRAINS WITH 12" (305) ROUND ADJUSTABLE TOPS																																																															
DRAWING NUMBER S2340	SIZE A	SCALE: NONE	DATE: 5-17-85	APPROVED BY: TD	CHECKED BY: TD	DRAWN BY: PJ	DIMENSIONS ARE SUBJECT TO MANUFACTURERS TOLERANCE AND CHANGE WITHOUT NOTICE		HEAVY DUTY DRAINS WITH TRACTOR GRATE FUNCTION: Used in heavy duty traffic areas where large top drain is required. Adjustable top collar permits accurate positioning of grate to meet finished floor level. A (Pipe Size) = 02(50), 03(80), 04(100), 05(125) or 06(150) ☐ Fig. 2340C . . . DEEP BODY CAULK OUTLET ☐ Fig. 2340Y . . . DEEP BODY NO-HUB OUTLET ☐ Fig. 2341C . . . SHALLOW BODY CAULK OUTLET ☐ Fig. 2345C . . . CAULK OUTLET ☐ Fig. 2345T . . . THREADED OUTLET <table border="1" style="width: 45%; font-size: 8px;"> <thead> <tr> <th rowspan="2">Figure</th> <th colspan="3">B</th> <th rowspan="2">C DIA</th> </tr> <tr> <th>Caulk</th> <th>Thread</th> <th>NO-HUB</th> </tr> </thead> <tbody> <tr> <td>2340</td> <td>5(125)</td> <td>3 3/4(95)</td> <td>5(125)</td> <td>15 1/4(390)</td> </tr> <tr> <td>2341</td> <td>3 3/4(95)</td> <td>3 3/4(95)</td> <td>—</td> <td>16(405)</td> </tr> </tbody> </table> <table border="1" style="width: 45%; font-size: 8px;"> <thead> <tr> <th>A SIZE</th> <th>02(50)</th> <th>03(80)</th> <th>04(100)</th> <th>05(125)</th> <th>06(150)</th> </tr> </thead> <tbody> <tr> <td>B</td> <td>6 7/8(175)</td> <td>6 3/8(162)</td> <td>5 7/8(149)</td> <td>5(125)</td> <td>4 1/2(115)</td> </tr> <tr> <td>C</td> <td>4 3/4(120)</td> <td>4 3/4(120)</td> <td>4 3/4(120)</td> <td>6 1/4(160)</td> <td>6 1/4(160)</td> </tr> <tr> <td>D</td> <td>6(150)</td> <td>6(150)</td> <td>6(150)</td> <td>6 5/8(168)</td> <td>6 7/8(175)</td> </tr> <tr> <td>E</td> <td>7 1/4(185)</td> <td>7 1/2(190)</td> <td>7 3/4(195)</td> <td>7 3/4(195)</td> <td>7 3/4(195)</td> </tr> <tr> <td>F</td> <td>8 5/8(220)</td> <td>8 3/4(220)</td> <td>8 3/4(220)</td> <td>8 1/2(215)</td> <td>8 1/2(215)</td> </tr> </tbody> </table> *This Dimension to Internal Stop of Speedi-Set Gasket. Δadd 1/8"(3) when bronze top is specified. REGULARLY FURNISHED: Duct Cast Iron Body and Flashing Collar with Adjustable Top and Tractor Grate. VARIATIONS: ☐ Adjustable Extensions 4 1/2(115) to 6"(150) -E ☐ Flat Bottom Strainer -FBS ☐ L Speedi-Set Service Weight ☐ LXH Speedi-Set Extra Heavy ☐ NO-HUB Adaptor (Specify Fig. 2646Y) (Fig. 2341-2345 only) ☐ Sediment Bucket -B ☐ Square Top -S ☐ Trap Primer Connection -P050 1/2"(13) & -P075 3/4"(19) (Fig. 2340 only) ☐ Vandal Proof Grate -U ☐ T Threaded Outlet ☐ Quad Close Trap Seal (Specify Fig. 2692) (Fig. 2340 & 2341 Only) OPTIONAL MATERIALS: ☐ Ductile Iron Grate -M ☐ Galvanized Cast Iron -G ☐ Nickel Bronze Top -NB ☐ Polished Bronze Top -PB NOTE: Dimensions shown in parentheses are in millimeters.		Figure	B			C DIA	Caulk	Thread	NO-HUB	2340	5(125)	3 3/4(95)	5(125)	15 1/4(390)	2341	3 3/4(95)	3 3/4(95)	—	16(405)	A SIZE	02(50)	03(80)	04(100)	05(125)	06(150)	B	6 7/8(175)	6 3/8(162)	5 7/8(149)	5(125)	4 1/2(115)	C	4 3/4(120)	4 3/4(120)	4 3/4(120)	6 1/4(160)	6 1/4(160)	D	6(150)	6(150)	6(150)	6 5/8(168)	6 7/8(175)	E	7 1/4(185)	7 1/2(190)	7 3/4(195)	7 3/4(195)	7 3/4(195)	F	8 5/8(220)	8 3/4(220)	8 3/4(220)	8 1/2(215)	8 1/2(215)
Figure	B			C DIA																																																												
	Caulk	Thread	NO-HUB																																																													
2340	5(125)	3 3/4(95)	5(125)	15 1/4(390)																																																												
2341	3 3/4(95)	3 3/4(95)	—	16(405)																																																												
A SIZE	02(50)	03(80)	04(100)	05(125)	06(150)																																																											
B	6 7/8(175)	6 3/8(162)	5 7/8(149)	5(125)	4 1/2(115)																																																											
C	4 3/4(120)	4 3/4(120)	4 3/4(120)	6 1/4(160)	6 1/4(160)																																																											
D	6(150)	6(150)	6(150)	6 5/8(168)	6 7/8(175)																																																											
E	7 1/4(185)	7 1/2(190)	7 3/4(195)	7 3/4(195)	7 3/4(195)																																																											
F	8 5/8(220)	8 3/4(220)	8 3/4(220)	8 1/2(215)	8 1/2(215)																																																											
FIGURE NUMBER 2340,2341,2345	F E D C	6-18-15 4-9-97 7-5-94 10-1-93	Revised Variations Added Millimeters Revised Submittal Update	TBW EMB CMB EMB	CL BS BS BS	WEIGHT POUNDS	VOLUME CUBIC FEET	FIGURE NUMBER 2340,2341,2345																																																								
REV.	DATE	DESCRIPTION			BY	CKD. BY																																																										



WARNING: Cancer and Reproductive Harm - www.P65Warnings.ca.gov