

D	JAY R. SMITH MFG. CO. MEMBER OF MORRIS GROUP INTERNATIONAL POST OFFICE BOX 3237 MONTGOMERY, ALABAMA 36109-0237 (USA) TEL: 334-277-8520 FAX: 334-272-7396 www.jrsmith.com MEMBER OF: MEMBER OF: MEMBER OF:				LOCATION 																																				
	TRAFFIC FLOOR DRAIN																																								
DRAWING NUMBER S2440	SIZE A	SCALE: NONE	DATE: 12-22-86	APPROVED BY: CR	CHECKED BY: TD	DRAWN BY: PL	WE CAN ASSUME NO RESPONSIBILITY FOR USE OF SUPERSEDED OR VOID DATA																																		
INTERNAL TRAP - SEDIMENT BUCKET FUNCTION: For heavy duty applications in boiler rooms and industrial plants, where water contains debris or salvageable materials which must be intercepted. The cleanout allows easy access to drainage lines where cleaning is necessary. Integral trap seal prevents sewer gases from entering building through drain.																																									
Free Area 47 Sq. In. 14 X 16 12 X 14 10 1/4 X 12 1/4 1 1/2 2 1/2 C 14 1/2 A B 2 Cleanout Plug A (PIPE SIZE) = 3, 4 or 6 Fig. 2440 . . . LESS FLASHING FLANGE Fig. 2445 . . . WITH FLASHING FLANGE <table border="1" style="margin: 10px auto; font-size: 8px;"> <tr> <td>A SIZE</td> <td>3</td> <td>4</td> <td>6</td> <td>3</td> <td>4</td> <td>6</td> <td>A SIZE</td> <td>3</td> <td>4</td> <td>6</td> </tr> <tr> <td>B SEAL</td> <td>5</td> <td>4 1/2</td> <td>3</td> <td>5</td> <td>4 1/2</td> <td>3</td> <td>C</td> <td>6 1/2</td> <td>6 1/2</td> <td>7</td> </tr> <tr> <td colspan="3"></td> <td colspan="3" style="text-align: center;">CAULK OUTLET</td> <td colspan="3"></td> <td colspan="2" style="text-align: center;">NO HUB</td> </tr> </table>									A SIZE	3	4	6	3	4	6	A SIZE	3	4	6	B SEAL	5	4 1/2	3	5	4 1/2	3	C	6 1/2	6 1/2	7				CAULK OUTLET						NO HUB	
A SIZE	3	4	6	3	4	6	A SIZE	3	4	6																															
B SEAL	5	4 1/2	3	5	4 1/2	3	C	6 1/2	6 1/2	7																															
			CAULK OUTLET						NO HUB																																
REGULARLY FURNISHED: All Galvanized Steel Body with Duco Finish, C.I. Removable Grate, C.I. Sediment Bucket and C.I. Internal Trap with Bronze Cleanout Plug. VARIATIONS: ☐ Flashing Device (C) (Fig. 2445 only) ☐ NO-HUB Outlet OPTIONAL MATERIALS: ☐ Polished Bronze Top (PB) ☐ Nickel Bronze Top (NB) ☐ Ductile Iron Grate (M) △ add 1/4" when bronze top is added																																									
FIGURE NUMBER	D C B A	10-2-91 10-11-90 7-11-90 5-30-90	Rev. Reg. Furn. & Opt. Mat. Rev. Dwg & Reg. Furn. Added Top View and Chg. Chart Redrawn & Added Optional NO-Hub	EMB TBW JLO JLO	SJM SJM SJM SJM	WEIGHT POUNDS	VOLUME CUBIC FEET	FIGURE NUMBER 2440, 2445																																	
REV.	DATE	DESCRIPTION			BY	CKD. BY																																			



WARNING: Cancer and Reproductive Harm - www.P65Warnings.ca.gov