



Artifacts™

66-1/8" x 32-1/2" freestanding bath
K-21000-B

Features

- Freestanding design creates a striking focal point in your bathing area
- Integral lumbar support on both ends
- Safeguard® slip-resistant surface provides excellent traction underfoot
- Coordinates with Artifacts faucets and accessories

Material

- KOHLER® enameled cast iron
- Painted exterior in Biscuit

Installation

- Freestanding

Required Products/Accessories

K-204 Ball-and-claw feet
K-7159 1-1/2" pop-up bath drain for freestanding baths

or

K-20027 Bath base for freestanding bath
K-7159 1-1/2" pop-up bath drain for freestanding baths

Recommended Products/Accessories

K-23726 Drain treatment
K-23725 Cast iron cleaner



Codes/Standards

ASME A112.19.1/CSA B45.2

KOHLER® Enameled Cast Iron Bath and Shower Base Lifetime Limited Warranty

See website for detailed warranty information.

Available Colors/Finishes

Color tiles intended for reference only.

Color	Code	Description
-------	------	-------------



96	Biscuit
----	---------





1-800-4KOHLER (1-800-456-4537)

Kohler Co. reserves the right to make revisions without notice to product specifications.

For the most current Specification Sheet, go to www.kohler.com USA or www.kohler.ca Canada

10-20-2025 20:07 - US/CA

THE BOLD LOOK
OF **KOHLER®**



Technical Information

All product dimensions are nominal.

Drain location:	Center
Basin area, bottom:	48-15/16" x 24-3/4" (1243 mm x 629 mm)
Basin area, top:	58-11/16" x 27-13/16" (1491 mm x 706 mm)
Weight:	389.5 lbs (176.7 kg)
Minimum floor load:	90 lbs/ft² (439.4 kg/m²)
Water depth:	14-3/8" (366 mm)
Water capacity:	69 gal (261.2 L)
Template:	Footprint, 1344921-7, required, not included

Notes

Measure your actual product for rough-in details.

Install this product according to the installation instructions.

The hot water supply should be 70% of the capacity of the bath or greater. Installations will vary.