



Mendota®
60" x 32" alcove bath, right drain
K-506

Features

- 59-1/2"L x 32"W x 16-1/4"H
- Standard 5' x 32" size for alcove installation
- Integral apron for quick installation
- Integral lumbar support
- Safeguard® slip-resistant surface provides excellent traction underfoot

Material

- KOHLER® enameled cast iron

Installation

- Alcove
- Integral flange
- Right drain

Required Products/Accessories

K-T37391 Rotary-turn bath drain trim
K-T37392 Rotary-turn bath drain trim

or

K-37383 Rough-in cable bath drain, PVC, 30" cable with tubing
K-78438 30" cable bath drain

Recommended Products/Accessories

K-1491 Bath/Whirlpool Pillow
K-1601 Bath/whirlpool footstop, removable
K-7213 27" Cable Bath Drain
K-7214 27" Cable Bath Drain
K-7259 Brass toe tap bath drain
K-706000-D3 Frameless Sliding Bath Door
K-706000-L 62" H sliding bath door with 1/4"-thick glass
K-706004-D3 Frameless Sliding Bath Door
K-706004-L Frameless Sliding Bath Door
K-23726 Drain treatment
K-23725 Cast iron cleaner



ADA

Codes/Standards

ASME A112.19.1/CSA B45.2
ASTM F462
ADA
ICC/ANSI A117.1

KOHLER® Enameled Cast Iron Bath and Shower Base Lifetime Limited Warranty

See website for detailed warranty information.

Available Colors/Finishes

Color tiles intended for reference only.

Color Code Description

	0	White
---	---	-------

Mendota®
60" x 32" alcove bath, right drain
K-506

The top view shows a rectangular bathtub with a finished wall. Dimensions include a total width of 60" (1524 mm), a finished wall thickness of 7/8" (22 mm), and a total depth of 32" (813 mm). The distance from the finished wall to the drain is 15-3/8" (391 mm), and the distance from the drain to the opposite wall is 8-1/2" (216 mm). The distance from the finished wall to the drain is 1-5/8" (41 mm).

The side view shows the bathtub's profile. The finished floor is 1/2" (13 mm) thick. The lumbar angle is 28°. The distance from the finished floor to the top of the tub is 16-1/4" (413 mm). The distance from the finished floor to the drain is 2-7/8" (73 mm). The distance from the drain to the opposite wall is 3" (76 mm). The distance from the drain to the top of the tub is 3-1/4" (83 mm). The drain is labeled as 1-1/2" Bath Drain and 1-1/2" NPT Thread.

Drain location:	Right
Basin area, bottom:	46" x 20" (1168 mm x 508 mm)
Basin area, top:	54" x 24" (1372 mm x 610 mm)
Weight:	351 lbs (159.2 kg)
Minimum floor load:	56 lbs/ft ² (273.4 kg/m ²)
Water depth:	10-7/8" (276 mm)
Water capacity:	45 gal (170.3 L)
Minimum flat for door:	1-7/8" (47 mm)

Measure your actual product for rough-in details.

Install this product according to the installation instructions.

The hot water supply should be 70% of the capacity of the bath or greater. Installations will vary.

ADA compliant when installed to the specific requirements of these regulations.