



Smart Heating Solutions



Commercial Unit Heaters

									
Item Number	KBP	SKB	KB	KB ECO2S	KB ECO2S+	KB PlatinumX	KBS	KFUH	KFUH ECO2S
Category	Unit Heater	Unit Heater	Unit Heater	Unit Heater	Unit Heater	Unit Heater	Unit Heater	Unit Heater	Unit Heater
Application	Up to 2 Car Garage	Up to 3 Car Garage	Large Facility Coverage	Up to 4 Car Garage	Up to 4 Car Garage	Large Facility Coverage	Up to 4 Car Garage	Large Facility Coverage	Large Facility Coverage
Max SqFt (8Ft Ceiling)	Up to 700 Sqft	Up to 1,000 Sqft	Up to 4,000 Sqft	Up to 1,500 Sqf	Up to 1,500 Sqf	Up to 4,000 Sqft	Up to 1,500 Sqft	Up to 3,500 Sqft	Up to 3,500 Sqft
Voltage	120/208/240/277/480	240	208/240/277/480	208/240	208/240	208/240/277/480	208/240/277/480	208/240/480	208/240/480
Wattages Available	950 - 6,000	5,000 - 10,000	4,000 - 20,000	4,000 - 15,000	4,000 - 15,000	3,000 - 40,000	3,000-40,000	3,800 - 70,000	3,800 - 70,000
Phasing Available	1PH or 1-3PH	1PH	1PH, 3PH or 1-3PH	1PH	1PH	1PH, 3PH or 1-3PH	1PH, 3PH or 1-3PH	1PH or 3PH	1PH or 3PH
Power Supply	Hardwired	Hardwired	Hardwired	Hardwired	Hardwired	Hardwired	Hardwired	Hardwired	Hardwired
BTU Output	3,242 - 20,478	17,000 - 34,100	11,263 - 68,260	13,652 - 51,195	13,500 - 51,200	10,239 - 136,520	10,200 - 136,500	12,800 - 238,900	12,799 - 238,910
CFM	270	520 - 800	520 - 1,750	520 - 1,050	520 - 1,050	520 - 3,500	520 - 3,500	832 - 4,308	708 - 4,284
Temperature Rise	11°F - 67°F	40°F - 44°F	20°F - 45°F	30°F - 45°F	30°F - 45°F	20°F - 45°F	20°F - 45°F	15°F - 51°F	8°F - 69°F
Air Throw	12 ft	16 ft - 24 ft	15 ft - 37 ft	15 ft - 33 ft	15 ft - 33 ft	15 ft - 43 ft	15 ft - 43 ft	60 ft - 110 ft	60 ft - 110 ft
Energy-Saving 2-Stage Heating	NO	NO	NO	YES	YES	NO	NO	Option Available	YES
Built-In Thermostat	Bi-Metal	Bi-Metal	Bi-Metal	Electronic	Electronic w/Remote Temperature Sensor	Electronic	Bi-Metal	NO	NO
24V Remote Thermostat Control	NO	NO	NO	NO	Connections Provided for 24V Remote Stat	Connections Provided for 24V Remote Stat	Option Available	Connections Provided for 24V Remote Stat	Connections Provided for 24V Remote Stat
Adjustable Louvers	NO	YES	YES	YES	YES	YES	YES	Accessory Sold Separately	Accessory Sold Separately
Power Indicator Light	NO	YES	NO	YES	YES	YES	NO	NO	NO
ON/OFF Switch	YES	NO	NO	YES	YES	YES	NO	NO	NO
High/Low	NO	YES (except 5kW)	NO	YES	YES	NO	NO	NO	NO
Fan Only Switch	YES	NO	NO	YES	YES	YES	NO	YES	YES
Built-In Timer	NO	NO	NO	1-9 Hours	1-9 Hours	1-9 Hours	NO	NO	NO
Element Construction	Pic-A-Watt	Spiral Fin	Spiral Fin	Spiral Fin	Spiral Fin	Spiral Fin	Spiral Fin	NiChrome Open Coil	NiChrome Open Coil
High Limit Safety Control	Self-Hold	Self-Hold	Self-Hold	Self-Hold	Self-Hold	Self-Hold	Self-Hold	Auto Reset	Auto Reset
Auto Fan Delay	YES	YES (except 5kW)	YES	YES	YES	YES	YES	NO	NO
Mounting Bracket	Wall / Ceiling	Wall / Ceiling	Wall / Ceiling	Wall / Ceiling	Wall / Ceiling	Wall / Ceiling	Wall / Ceiling	Brackets for Threaded Rod	Brackets for Threaded Rod
Instruction Manual	YES	YES	YES	YES	YES	YES	YES	YES	YES
Mounting Diagram	YES	YES	YES	YES	YES	YES	YES	YES	YES
Warranty	5 Year	3 Year	5 Year	5 Year	5 Year	5 Year	5 Year	5 Year	5 Year
Factory Tech Support	YES	YES	YES	YES	YES	YES	YES	YES	YES
Electronic Controls	NO	NO	NO	YES	YES	YES	YES	NO	NO
Remote Control	NO	NO	NO	YES	YES	YES	YES	NO	NO
Made In USA	YES	YES	YES	YES	YES	YES	YES	YES	YES

king-electric.com

