



Brenham™

Wall-mount Bathroom Lavatory With Shroud

K-1999-SS4

Features

- Antimicrobial finish inhibits the growth of mold-, mildew-, stain-, and odor-causing bacteria on the fixture surface. This product does not protect users against bacteria, viruses, or other disease organisms. Always clean and wash this product thoroughly before and after each use
- Ideal for healthcare and education installations
- 4" (102 mm) centerset faucet holes
- Oval basin
- Overflow drain
- Includes wall hanger
- Combination consists of the K-1997-SS4 basin and the K-1998-SS shroud

Material

- Vitreous china

Installation

- Wall-mount
- Drilled for concealed arm carrier installation

Recommended Products/Accessories

K-23726 Drain treatment
K-23725 Cast iron cleaner

Optional Products/Accessories

K-8998 P-Trap



ADA

CSA B651

OBC

Codes/Standards

ASME A112.19.2/CSA B45.1
ADA
ICC/ANSI A117.1
CSA B651
OBC

KOHLER® Vitreous China Bathroom Sink Lifetime Limited Warranty


See website for detailed warranty information.

Available Colors/Finishes

Color tiles intended for reference only.

Color Code Description

	0	White
---	---	-------



Technical drawing of the 1000 Series Locking Device, showing front and side views with dimensions in inches and millimeters.

Front View Dimensions:

- Top Left: 8-9/16" (217 mm)
- Top Center: 3-5/16" (84 mm)
- Top Right: 2-11/16" (68 mm)
- Left Side: 13-13/16" (351 mm)
- Right Side: 19-3/4"
- Center Right: 7-15/16" (202 mm)
- Bottom Right: Ø 1-3/16" (30 mm) (502 mm) Locking Device Holes
- Bottom Center: 18-5/16" (465 mm)
- Bottom Left: 22-3/16" (564 mm)
- Bottom Left (Leveling Screw Hole): Ø 1-1/4" (32 mm) Leveling Screw Hole

Side View Dimensions:

- Top Left: 9/16" (14 mm)
- Top Center: 9-1/4" (235 mm)
- Top Right: 2-5/8" (67 mm)
- Right Side: 29-1/8" (740 mm)
- Center Right: 6-1/2" (165 mm)
- Bottom Right: 9-3/4" (248 mm)
- Bottom Right: 7-3/4" (197 mm)
- Bottom Right: 28-1/2" (724 mm)
- Bottom Center: 3-1/2" (89 mm)
- Bottom Left: 4" (102 mm)
- Bottom Left: 31" (787 mm)
- Bottom Left: 4" (102 mm)
- Bottom Left: 3/8" Hot
- Bottom Left: 1-1/4" OD
- Bottom Left: 3/8" Cold
- Bottom Left: Ø 5/16" (8 mm) Hole in brackets

	ADA and TAS	Children's Environment ADA and TAS Ages 6-12 yrs
A	34" (864 mm)	31" (787 mm)
B	27" (686 mm)	24" (610 mm)
C	11" (279 mm)	11-1/16" (281 mm)
D	9" (229 mm)	9-1/16" (230 mm)
E	8" (203 mm)	8-1/16" (205 mm)

Drain hole: 1-3/4" (44 mm)

ADA, OBC, CSA B651 compliant when installed to the specific requirements of these regulations.