

Features

- Digitally controlled
- High-temperature limit setting for added safety
- One touch control of two valve outlets
- Low-profile design
- Selectable water-saving functionality
- Selectable Fahrenheit or Celsius
- Selectable outlet delivery
- Easy-to-read LCD display and raised one-touch buttons
- Use for single- or dual-outlet applications, including bath and shower, shower-only, or bath-only experiences
- Integrated diverter with touch-button operation toggles between water outlets, running them separately or simultaneously
- Allows user to add a second control for convenience and flexibility
- Warm-up mode pauses the shower flow when the water is brought up to the preferred temperature, and then notifies you that the shower is ready to enter, thus conserving water
- Pause feature temporarily pauses water flow to conserve water while you lather, shave, or shampoo
- Countdown mode allows you to set the duration of the shower to easily manage both time and water use

Installation

- Mounts on finished wall surface

Required Products/Accessories

K-528-PM Two-port digital thermostatic valve

Recommended Products/Accessories

K-23723 Faucet cleaner


ADA

Codes/Standards

UL 1951
CSA C22.2 No. 14
CSA C22.2 No. 68
ADA
ICC/ANSI A117.1

KOHLER® Electronic Faucets, Valves, and Controls Five-Year Limited Warranty

See website for detailed warranty information.



Technical Information

All product dimensions are nominal.

Notes

Install this product in accordance with the installation instructions.

Recommended installation height 58" (1473 mm) from floor to center of interface.

ADA compliant when installed to the specific requirements of these regulations.