



Primary™

Elongated Floor Mount, Flushometer Bowl
K-96064-SS

Features

- Elongated, 10-1/2" height bowl.
- Antimicrobial finish inhibits the growth of mold-, mildew-, stain-, and odor-causing bacteria on the fixture surface. This product does not protect users against bacteria, viruses, or other disease organisms. Always clean and wash this product thoroughly before and after each use.
- 10" x 7" (254 mm x 178 mm) water surface.
- 1-7/8" (48 mm) fully glazed trapway.
- 10" or 12" (254 or 305 mm) rough-in.
- 1.28 gpf - 1.6 gpf (4.8 - 6.0 lpf) flush range.
- Includes K-4686 toilet seat with scalloped handhold locations.
- 1-1/2" (38 mm) top spud.

Material

- Vitreous china.

Technology

- Designed to outperform competitors in bowl cleanliness and plug resistance.
- Excellent bowl rinse.
- Maximum drain line carry at 1.28 gpf per ASME Standard.

Installation

- Children's height bowl.
- Replaces Primary K-4321 and K-4384. Height and footprint may vary.

Water Conservation & Rebates

- The ultra-low water consumption is ideal for water conservation and can help earn Water Efficiency points in the LEED® Green Building Rating System.

Included Components

Additional Components:

- Bolt cap accessory pack
- Spud



ADA

Codes/Standards

ASME A112.19.2/CSA B45.1
DOE - Energy Policy Act 1992
EPA WaterSense®
California Energy Commission (CEC)
ADA
ICC/ANSI A117.1

KOHLER® One-Year Limited Warranty

See website for detailed warranty information.

Available Colors/Finishes

Color tiles intended for reference only.

Color	Code	Description
-------	------	-------------



0	White
---	-------

