

Certifications	Part No.	Size	Configuration	Model	Cs.	Ct.
----------------	----------	------	---------------	-------	-----	-----

T-4111NL

No Lead Cast Bronze Water Service Extra Strong Lead Connection x MNPT Adapter

100 psi - 100° F Max.
NSF / ANSI 61
AWWA C800



313-614NL	5/8" x 3/4"	Extra Strong x MNPT	T-4111NL	48	6
313-615NL	3/4"	Extra Strong x MNPT	T-4111NL	24	4

T-4112NL

No Lead Bronze Lead Connection Pack Joint x Extra Strong Coupling

100 psi - 100° F Max.
NSF / ANSI 61
AWWA C800



313-625NL	5/8" x 3/4"	Extra Strong x Pack (CTS)	T-4112NL	36	6
-----------	-------------	---------------------------	----------	----	---

Meter Couplings

T-4214NL

No Lead Cast Brass Water Service MNPT x AWWA Meter Coupling

100 psi - 100° F Max.
NSF / ANSI 61
AWWA C800



313-123NL	1/2"	MNPT x AWWA	T-4214NL	160	20
313-124NL	3/4"	MNPT x AWWA	T-4214NL	100	20
313-125NL	1"	MNPT x AWWA	T-4214NL	80	10
313-127NL	1-1/2"	MNPT x AWWA	T-4214NL	24	6
313-128NL	2"	MNPT x AWWA	T-4214NL	24	6

T-4215NL

No Lead Cast Bronze Water Service MNPT x AWWA Meter Coupling

100 psi - 100° F Max.
NSF / ANSI 61
AWWA C800



313-133NL	1/2"	MNPT x AWWA	T-4215NL	80	20
313-134NL	3/4"	MNPT x AWWA	T-4215NL	80	20
313-135NL	1"	MNPT x AWWA	T-4215NL	60	15

Meter Flanges

T-4216NL

No Lead Cast Bronze Water Service Meter Flange

80 psi - 100° F Max. temp
AWWA C800



313-707NL	1-1/2"	FNPT x Flange	T-4216NL	16	8
313-708NL	2"	FNPT x Flange	T-4216NL	32	8

Gaskets and hardware not included.