

Certifications	Part No.	Size	Configuration	Model	Cs.	Ct.
----------------	----------	------	---------------	-------	-----	-----

T-441NL / T-442NL

...Continued



T-442NL Meter Angle Valve with Drain

111-113NL	3/4" x 1/2"	Flare x FNPT	T-442NL	48	8
111-114NL	3/4" x 3/4"	Flare x FNPT	T-442NL	48	8
111-115NL	1" x 3/4"	Flare x FNPT	T-442NL	36	6
111-116NL	1" x 1"	Flare x FNPT	T-442NL	24	4

T-443NL

No Lead Forged Brass
1/4-Turn Meter Valve

NSF / ANSI 61
AWWA C800
400 CWP



111-123NL	3/4" x 3/4"	FNPT x Flare	T-443NL	20	2
111-124NL	3/4" x 1"	FNPT x Flare	T-443NL	20	2
111-125NL	1" x 1"	FNPT x Flare	T-443NL	20	2

Pack Joint Adapters

T-4300NL

No Lead Cast Bronze Water
Service CTS Pack Joint x
MNPT Adapter

1/2" - 1" 100 psi - 100° F Max.
1-1/4" - 2" 80 psi - 100° F Max.
ANSI / NSF 61
AWWA C800



313-203NL	1/2"	Pack (CTS) x MNPT	T-4300NL	72	12
313-204NL	3/4"	Pack (CTS) x MNPT	T-4300NL	60	10
313-205NL	1"	Pack (CTS) x MNPT	T-4300NL	48	6
313-206NL	1-1/4"	Pack (CTS) x MNPT	T-4300NL	24	4
313-207NL	1-1/2"	Pack (CTS) x MNPT	T-4300NL	16	4
313-208NL	2"	Pack (CTS) x MNPT	T-4300NL	8	2
313-209NL	3/4" x 1"	Pack (CTS) x MNPT	T-4300NL	36	6
313-210NL	1" x 3/4"	Pack (CTS) x MNPT	T-4300NL	24	4
313-211NL	1-1/4" x 1"	Pack (CTS) x MNPT	T-4300NL	24	4

T-4320NL

No Lead Cast Bronze Water
Service IPS/PEP Pack Joint x
MNPT Adapter

100 psi - 100° F Max.
ANSI / NSF 61
AWWA C800



313-234NL	3/4"	Pack (IPS) x MNPT	T-4320NL	48	6
313-239NL	3/4" x 1"	Pack (IPS) x MNPT	T-4320NL	60	10
313-235NL	1"	Pack (IPS) x MNPT	T-4320NL	24	4
313-236NL	1"	Pack (IPS) x MNPT	T-4320NL	24	4