



LEGEND

PLUMBING • INDUSTRIAL • COMMERCIAL • HYDRONICS

Push Fit Fittings

Price List LT-PFF0616

Effective Date: June 28, 2016



Downstream
Thinking

It's all about Performance™

InstaLoc II™ Push Fit Ball Valve

200 CWP, max temp 250°F
No lead / DZR forged brass, full port
ANSI / NSF 61-G, NSF 14, ASSE 1061



P-2200NL



P-2200NL Drop Ear



P-2200NL

	Part No.	Size	Configuration	Model	List Price	Case	Carton
	456-003NL	1/2"	Push	P-2200NL	20.17	100	10
	456-004NL	3/4"	Push	P-2200NL	27.37	100	10
	456-005NL	1"	Push	P-2200NL	42.04	50	5
NEW	456-023NL	1/2"	Push x Push	P-2200NL Drop Ear	21.81	100	10
NEW	456-024NL	3/4"	Push x Push	P-2200NL Drop Ear	31.25	100	10
NEW	456-025NL	1"	Push x Push	P-2200NL Drop Ear	55.47	50	5
NEW	456-013NL	1/2"	Push x FNPT	P-2200NL	21.25	100	10
NEW	456-014NL	3/4"	Push x FNPT	P-2200NL	29.89	100	10
NEW	456-015NL	1"	Push x FNPT	P-2200NL	58.28	50	5

InstaLoc II™ Push Fit Fittings

200 CWP, max temp 250°F
No lead / DZR forged brass
ANSI / NSF 61-G, NSF 14, ASSE 1061



Push Elbow



Push x FNPT
Elbow



Push x MNPT
Elbow



Push x FNPT
Tee

Elbows

456-053NL	1/2"	Push	Elbow	11.21	80	20
456-084NL	3/4" x 1/2"	Push	Elbow	17.98	60	15
456-054NL	3/4"	Push	Elbow	18.43	60	15
456-055NL	1"	Push	Elbow	29.94	30	15

456-063NL	1/2"	Push x FNPT	Elbow	11.82	90	15
456-064NL	3/4"	Push x FNPT	Elbow	19.42	60	15
456-065NL	1"	Push x FNPT	Elbow	21.89	30	15

456-073NL	1/2"	Push x MNPT	Elbow	11.64	90	15
456-074NL	3/4"	Push x MNPT	Elbow	18.14	60	15
456-075NL	1"	Push x MNPT	Elbow	23.29	30	15

Tees

456-160NL	1/2"	Push x FNPT	Tee	19.25	100	25
456-161NL	3/4"	Push x FNPT	Tee	28.55	50	25

InstaLoc II™ Push Fit Fittings (cont.)

200 CWP, max temp 250°F
No lead / DZR forged brass
ANSI / NSF 61-G, NSF 14, ASSE 1061



Push x MNPT
Tee



Push Tee



Tee w/ Valve



Tee w/ 3/8" OD
Valve



Drop Ear Tee
w/ Valve



Drop Ear Tee w/
3/8" OD Valve



Test Cap
Push



Slip Coupling
Push

Part No.	Size	Configuration	Model	List Price	Case	Carton
456-170NL	1/2"	Push x MNPT	Tee	15.64	120	20
456-171NL	3/4"	Push x MNPT	Tee	22.39	60	20
456-180NL	1/2"	Push	Tee	14.87	60	20
456-181NL	1/2" x 3/4"	Push	Tee	22.33	60	15
456-182NL	1/2" x 1"	Push	Tee	28.36	60	15
456-183NL	3/4" x 1/2" x 1/2"	Push	Tee	21.48	60	15
456-184NL	3/4" x 3/4" x 1/2"	Push	Tee	23.64	60	15
456-185NL	3/4" x 1/2" x 3/4"	Push	Tee	20.56	60	15
456-186NL	3/4"	Push	Tee	21.91	60	15
456-187NL	1" x 3/4"	Push	Tee	37.03	24	12
456-188NL	1"	Push	Tee	37.39	24	12

Drop Ear Tee with Icemaker Connection Valve

NEW	456-153NL	1/2" x 1/2" x 1/4"	Push x Comp	DE Tee w/ Valve	21.06	60	15
NEW	456-151NL	3/4" x 3/4" x 1/4"	Push x Comp	DE Tee w/ Valve	24.39	60	15

Tee with Icemaker Connection Valve

NEW	456-155NL	1/2" x 1/2" x 1/4"	Push x Comp	Tee w/ Valve	19.96	60	15
NEW	456-157NL	3/4" x 3/4" x 1/4"	Push x Comp	Tee w/ Valve	22.10	60	15

Drop Ear Tee with 3/8" OD Connection Valve

NEW	456-154NL	1/2" x 1/2" x 3/8"	Push x Comp	DE Tee w/ Valve	22.61	60	15
NEW	456-152NL	3/4" x 3/4" x 3/8"	Push x Comp	DE Tee w/ Valve	24.70	60	15

Tee with 3/8" OD Connection Valve

NEW	456-156NL	1/2" x 1/2" x 3/8"	Push x Comp	Tee w/ Valve	20.57	60	15
NEW	456-158NL	3/4" x 3/4" x 3/8"	Push x Comp	Tee w/ Valve	22.20	60	15

Test Caps

456-483NL	1/2"	Push	Test Cap	6.92	120	30
456-484NL	3/4"	Push	Test Cap	11.21	60	20
456-485NL	1"	Push	Test Cap	12.94	30	15

Slip Couplings

456-503NL	1/2"	Push	Slip Coupling	21.31	60	15
456-504NL	3/4"	Push	Slip Coupling	28.92	60	15
456-505NL	1"	Push	Slip Coupling	44.19	45	15

InstaLoc II™ Push Fit Fittings (cont.)

200 CWP, max temp 250°F
No lead / DZR forged brass
ANSI / NSF 61-G, NSF 14, ASSE 1061



Coupling



Push x FNPT
Adapter



Push x MNPT
Adapter



Disconnect Tool

Couplings

456-523NL	1/2"	Push	Coupling	9.97	80	20
456-524NL	3/4" x 1/2"	Push	Coupling	13.00	60	15
456-525NL	3/4"	Push	Coupling	12.97	60	15
456-526NL	1" x 3/4"	Push	Coupling	23.86	30	15
456-527NL	1"	Push	Coupling	21.92	30	15

Adapters

456-703NL	1/2"	Push x FNPT	Adapter	8.19	80	20
456-704NL	1/2" x 3/4"	Push x FNPT	Adapter	11.28	60	15
456-705NL	3/4"	Push x FNPT	Adapter	11.86	60	15
456-706NL	1" x 3/4"	Push x FNPT	Adapter	19.33	30	15
456-707NL	1" x 1"	Push x FNPT	Adapter	20.64	30	15

456-753NL	1/2"	Push x MNPT	Adapter	7.92	80	20
456-754NL	1/2" x 3/4"	Push x MNPT	Adapter	11.53	60	15
456-755NL	3/4"	Push x MNPT	Adapter	11.62	60	15
456-756NL	1" x 3/4"	Push x MNPT	Adapter	19.15	30	15
456-757NL	1" x 1"	Push x MNPT	Adapter	22.61	30	15

Disconnect Tool

456-803NL	1/2"	-	Disconnect Tool	2.75	500	100
456-804NL	3/4"	-	Disconnect Tool	2.75	500	100
456-805NL	1"	-	Disconnect Tool	3.03	250	50

Turn-n-Loc™ Plastic Push Ball Valve

Naturally lead free
Full port 100 psi @ 150°F
ANSI / NSF 61-G, NSF 14, ASSE 1061



Push x Push Ball
Valve

NEW	465-082	3/8"	Push x Push	Ball Valve	13.17	80	80
NEW	465-083	1/2"	Push x Push	Ball Valve	16.03	60	60
NEW	465-084	3/4"	Push x Push	Ball Valve	18.94	40	40

Turn-n-Loc™ Plastic Push Fittings

Naturally lead free
150 psi @ 140°F & 100 psi @ 180°F max temp
ANSI / NSF 61-G, NSF 14, ASSE 1061



Drop Ear Elbow



Push x FNPT
Adapter



Elbow



Swivel Elbow - Brass



Elbow



Push x MNPT
Adapter



Swivel Elbow



Swivel Coupling w/
Brass Nut

Drop Ear Elbows

465-001	3/8"	Push x FNPT	Drop Ear Elbow	8.36	180	30
465-002	1/2"	Push x FNPT	Drop Ear Elbow	8.30	180	30

Adapters

465-005	3/8" x 1/2"	Push x FNPT	Adapter	5.92	300	50
465-006	1/2"	Push x FNPT	Adapter	7.51	300	5
465-007	1/2" x 3/4"	Push x FNPT	Adapter	7.93	240	40
465-008	3/4"	Push x FNPT	Adapter	10.02	180	30
465-009	1"	Push x FNPT	Adapter	13.21	120	20

465-010	1/2" x 3/4"	Push x FGHT	Adapter	8.63	120	20
---------	-------------	-------------	---------	------	-----	----

465-013	3/8" x 1/2"	Push x MNPT	Adapter	5.89	300	50
465-014	1/2"	Push x MNPT	Adapter	5.99	300	50
465-015	1/2" x 3/4"	Push x MNPT	Adapter	6.76	240	40
465-016	3/4"	Push x MNPT	Adapter	8.93	180	30
465-017	1"	Push x MNPT	Adapter	10.19	120	20

Elbows

465-019	1/2"	Push x MNPT	Elbow	6.68	300	50
---------	------	-------------	-------	------	-----	----

Swivel Elbows

465-020	1/2"	Push x FNPT	Swivel Elbow	6.59	240	40
465-021	1/2" x 3/4"	Push x FGHT	Swivel Elbow	8.66	240	40
465-022	1/2"	Push x Closet	Swivel Elbow	7.58	240	40

Swivel Elbows - Brass

465-025	1/2"	Push x FNPT	Swivel Elbow	13.44	240	40
465-026	1/2" x 3/4"	Push x FGHT	Swivel Elbow	18.47	240	40
465-027	1/2"	Push x FNPT	Swivel Elbow	17.61	240	40

Swivel Couplings

465-030	1/2"	Push x FNPT	Swivel Coupling	6.97	240	40
465-031	1/2" x 3/4"	Push x FGHT	Swivel Coupling	8.23	240	40
465-032	1/2"	Push x Closet	Swivel Coupling	7.40	240	40

Swivel Couplings with Brass Nut

465-035	1/2"	Push x FNPT	Swivel Coupling	12.80	240	40
465-036	1/2" x 3/4"	Push x FGHT	Swivel Coupling	18.04	240	40
465-037	1/2"	Push x Closet	Swivel Coupling	16.92	240	40

Elbows

465-046	1/2"	Push x Push	Elbow	7.34	240	40
465-047	3/4"	Push x Push	Elbow	9.96	180	30

Turn-n-Loc™

Naturally lead free
150 psi @ 140°F & 100 PSI @ 180°F max temp
ANSI / NSF 61-G, NSF 14, ASSE 1061



Coupling



Tee

Part No.	Size	Configuration	Model	List Price	Case	Carton
Couplings						
465-054	1/2"	Push x Push	Coupling	7.09	240	40
465-055	3/4"	Push x Push	Coupling	9.58	180	30
465-056	1"	Push x Push	Coupling	14.34	120	20
Reducing Couplings						
465-058	1/2" x 3/8"	Push x Push	Reducing Coupling	7.09	240	40
465-059	3/4" x 1/2"	Push x Push	Reducing Coupling	8.71	180	30
465-060	1" x 3/4"	Push x Push	Reducing Coupling	12.56	120	20
Tees						
465-063	1/2"	Push x Push	Tee	10.14	180	30
465-064	3/4"	Push x Push	Tee	13.33	120	20
465-070	3/4" x 3/4" x 1/2"	Push x Push	Tee	13.18	120	20

Mini-Loc™ Plastic Push Ball Valve

Naturally lead free
150 psi @ 140°F & 100 psi @ 180°F max temp
ANSI / NSF 61-G, NSF 14, ASSE 1061



Push x MNPT
Straight Ball Valve



Push x Push Straight
Ball Valve



Push x FNPT
Angle Ball Valve

NEW	465-071	1/4"	Push x FNPT	Angle Ball Valve	7.72	50	-
NEW	465-072	3/8"	Push x FNPT	Angle Ball Valve	8.33	50	-
NEW	465-075	1/4"	Push x MNPT	Straight Ball Valve	7.72	50	-
NEW	465-076	3/8"	Push x MNPT	Straight Ball Valve	8.33	50	-
NEW	465-079	1/4"	Push x Push	Straight Ball Valve	7.72	50	-
NEW	465-080	3/8"	Push x Push	Straight Ball Valve	8.33	50	-

Mini-Loc™ Plastic Push Fittings

Naturally lead free

ANSI / NSG 61-G, NSF 14, ASSE 1061

FDA compliant

1/4" / 230 psi @ 34°F to 68°F, 150 psi @ 150°F

3/8" / 170 psi @ 34°F to 68°F, 100 psi @ 150°F



Male Adapter



Tee



Female Adapter



Elbow



Coupling

Male Adapters

465-091	1/4" x 1/4"	Push x MNPT	Male Adapter	1.99	800	200
465-092	3/8" x 1/4"	Push x MNPT	Male Adapter	2.35	800	200
465-093	3/8" x 3/8"	Push x MNPT	Male Adapter	2.59	800	200

Male Elbows

465-103	3/8" x 1/4"	Push x MNPT	Male Elbow	2.59	800	200
465-104	3/8" x 3/8"	Push x MNPT	Male Elbow	2.69	800	200

Tees

465-110	1/4"	Push	Tee	3.59	800	200
465-111	3/8"	Push	Tee	3.99	800	200

Female Adapters

465-116	1/4" x 1/4" *	Push x Comp	Adapter	2.66	800	200
465-117	3/8" x 1/4" *	Push x Comp	Adapter	3.56	800	200

* UNS 7/16"-24

Elbows

465-120	1/4"	Push x Push	Elbow	2.36	800	200
465-121	3/8"	Push x Push	Elbow	3.68	800	200

Couplings

465-140	1/4"	Push x Push	Coupling	2.29	800	200
465-142	3/8" x 1/4"	Push x Push	Coupling	3.23	800	200
465-143	3/8"	Push x Push	Coupling	3.48	800	200

All Mini-Loc™ fittings are in bags of 50.



300 N. Opdyke Rd.

Auburn Hills, MI 48326

phone: 800-752-2082

fax: 800-835-4457

web: www.legendvalve.com

email: service@legendvalve.com



LT-PFF0616