

Brass & PPSU Cold Expansion PEX Fittings



For PEX fittings systems utilizing cold expansion, Legend offers several configurations in sizes from 3/8" to 2" in no lead brass and 1/2" to 2" in plastic. The assortment includes PEX-a rings, PPSU multi-port tees commonly used in remote manifold plumbing systems. Both the no lead/ DZR forged brass and PPSU (polyphenylsulfone) PEX fittings are manufactured to meet ASTM F1960. They are third party certified ANSI/NSF 61 and ANSI/NSF 14.

HyperPure Bimodal PE-RT Tubing in diameters up to 1-1/2" inch are compatible with F1960 cold expansion. We do not recommend expanding the 2" diameter HyperPure tubing, as it is not compatible with this fitting system. See page 170 for more information about HyperPure tubing.

Certifications	Part No.	Size	Configuration	Cs.	Ct.
----------------	----------	------	---------------	-----	-----

PEX-A F1960 PEX Cold Expansion Rings

Third-party tested and certified;
NSF/ANSI 61 & 14
ASTM F1960



460-923	1/2"	PEX (F1960); Bag of 50	20	1
460-924	3/4"	PEX (F1960); Bag of 50	10	1
460-925	1"	PEX (F1960); Bag of 50	5	1
460-926	1-1/4"	PEX (F1960); Bag of 10	15	1
460-927	1-1/2"	PEX (F1960); Bag of 5	25	1
460-928	2"	PEX (F1960); Bag of 5	10	1

No Lead DZR Forged Brass Cold Expansion PEX x CPVC Transition Fitting

Third-party tested and certified;
NSF/ANSI 61 & 14
ASTM F1960



302-453NL	1/2"	PEX (F1960) x CPVC		
302-454NL	3/4"	PEX (F1960) x CPVC		
302-455NL	1"	PEX (F1960) x CPVC		

No Lead DZR Forged Brass Cold Expansion PEX x Fitting Adapter

Third-party tested and certified;
NSF/ANSI 61 & 14
ASTM F1960



462-613NL	1/2"	PEX (F1960) x Fitting	250	50
462-614NL	3/4"	PEX (F1960) x Fitting	250	25
462-615NL	1"	PEX (F1960) x Fitting	120	15
462-616NL	1-1/4"	PEX (F1960) x Fitting	100	10
462-617NL	1-1/2"	PEX (F1960) x Fitting	80	10
462-618NL	2"	PEX (F1960) x Fitting	40	5

NL F1960 PEX x Fitting Reducing Adapter

462-619NL	3/4" x 1/2"	PEX (F1960) x Fitting	200	25
462-620NL	1" x 3/4"	PEX (F1960) x Fitting	200	25