

Notchers



Malco®

Work. Perform. Outlast.
Limited Lifetime Warranty



N1R

Fast and easy cutting. Notcher makes a clean 30° “V” shaped cut in sheet metal.

13/16 in. (20.6 mm) maximum throat depth. Upper cutting jaw is drop forged high impact alloy steel. Hook design of cutting jaw facilitates notching corners or take-off tabs to desired depth without slipping. Long-wearing, hardened stamped steel components feature rust-resistant nickel plate and black oxide finishes.



Ergonomic Redline Handles with unique one-hand operation latch offer maximum compound leverage performance and natural fit and feel.

One-Inch Notcher



N2R

Provides more clearance for folding and fabricating metal ductwork



The N2R Notcher punches a big 1 in. (25.4 mm) deep “V” notch in common 24 to 30 ga. (0.71-0.41 mm) galvanized sheet metal quickly and easily.

Folding and fabricating metal ductwork is easier than ever with the full 1 inch clearance that the N2R single operation notcher provides. Precision-ground steel upper jaw and hardened stamped steel components feature rust-resistant black oxide and nickel plated finishes.

Snap Lock Punch



SL1R



Join sheet metal, duct, and pipe sections economically.

No need for extra hardware. Punches raise a louvered shaped projection on metal edge for locking into rolled edge of sheet or piece to be joined. Metal pieces snap together and are fastened securely. Compound Handle Leverage for maximum ease of operation. Punch impression spaced 3/8 in. from edge of metal. Heavy forged cutting jaw. Rust-resistant nickel plate and black oxide finishes.



CAPACITIES	Material	Aluminum	Copper	Stainless Steel 26 Gauge	Galvanized Steel 24 Gauge	Mild Steel 24 Gauge
N1R	inches (mm)	0.035 (0.89)	0.023 (0.58)	0.018 (0.46)	0.028 (0.71)	0.024 (0.61)
N2R	inches (mm)	0.035 (0.89)	0.023 (0.58)	0.018 (0.46)	0.028 (0.71)	0.024 (0.61)
SL1R	inches (mm)	0.035 (0.89)	0.023 (0.58)	0.018 (0.46)	0.028 (0.71)	0.024 (0.61)
Replacement Spring for Hand Tools						
5018	Fits N1R, N2R, SL1R					