

Location: _____



MC-31

HANGER PLATE CARRIER WITH BEARING PLATE AND TWO UPRIGHTS

Specification: MIFAB® Series MC-31 single lavatory hanger plate carrier with universal, adjustable, top support plate. Complete with lacquered 2" x 1" x 1/8" thick structural steel uprights with 3" x 4 1/2" welded steel feet and mounting hardware.

Function: Used to support wall-hung fixtures such as urinals and water coolers that are independent of the wall. Designed for use in conjunction with the fixture hanger plate supplied by the fixture manufacturer.

CUTOUT FOR FIXTURE
WITH BACK SUPPLY

SINGLE UNIVERSAL PLATE
ASSEMBLY, SECURED TO
UPRIGHTS WITH "U" BOLTS
TO PROVIDE EASE OF ROUGH-
IN HEIGHT ADJUSTMENT

(1/4")-20 x 8" ALL
THREADED PLATED
RODS (6 PIECES)
W / HARDWARE

EXTRA HEAVY
RECTANGULAR STEEL
STRUCTURAL UPRIGHTS
(2" x 1" x 1/8"
Wall Thickness)

HEAVY DUTY WELDED
FEET THAT FIT
WITHIN STANDARD
STUD WALL CONSTRUCTION


42"

3" 4 1/2"



MC-31 Series Meets ANSI/ASME fixture carrier standard A112.6.1M-97

**NOTE: FOOT SUPPORTS SHOULD BE SECURELY ANCHORED TO FLOOR WITH
1/2" (13) BOLTS AND ANCHORS BY OTHERS.**

Note: See the various fixture dimensional rough-in guides on the www.mifab.com website.



BASE DETAIL



SUFFIX	OPTIONAL VARIATIONS
☐ -A	Stud length over 8" (specify)
☐ -B	Floor to ceiling uprights
☐ -BA	Buy American Act compliant product
☐ -C	Two hanger plates (three uprights for corner mounted lavatory)
☐ -HDH	Heavy Duty hanger

☐ -PA	Pennsylvania Steel Act compliant product
☐ -PFAB	Prefabricated carrier
☐ -SL	3/4" Slots in legs – to receive 1/2" water piping through legs
☐ see MC-31D	Back to back system
☐ -20	Flush valve support

CALIFORNIA PROPOSITION 65 WARNING. This product contains chemicals known to the State of California to cause cancer and birth defects or other reproductive harm.

Job Name: _____

Page No: _____

Section No: _____

Contractor: _____

Schedule No: _____

Purchase Order No: _____