

Location: _____




F1100-C-DD

**FLOOR DRAIN WITH ANGLE STRAINER
FOR MEMBRANE FLOOR AREAS**

Specification: MIFAB® Series F1100-C-DD lacquered cast iron hub drain with anchor flange, cast iron membrane clamp ring with primary and secondary weepholes for waterproofing membrane, and standard (specify material finish) indirect waste hub. (For non-membrane floors, use MIFAB F1100-DD Series.)

Function: Used in restaurants, hospitals, industrial laboratories, and other membrane finished areas where indirect waste lines above the floor drip condensate or waste water into the hub. Membrane clamp is provided to secure the waterproofing membrane.



PARTS:



A1 BODY



DD-(*)
(*) Denotes strainer finish (-1, -3 or -50)



A1-C1



HS-1

F1100-C-DD Series meets
ANSI-ASME floor
drain standard
A112.6.3-2001

HUB ADJUSTMENT		PIPE SIZE	BODY HEIGHT				
			NO HUB (STANDARD)	PUSH ON (P)	THREADED (T)	INSIDE CAULK (X)	PVC/ABS (-30)/(-31)
1 1/2" (38)	2 5/8" (66)	2" (51) ○	3" (76) □	3 3/8" (86) □	2 1/4" (57) □	3 3/4" (95) □	2 15/16" (75) □
		3" (76) ○	3" (76) □	3 3/8" (86) □	2 5/8" (67) □	3 3/4" (95) □	3 3/4" (95) □
		4" (102) ○	3" (76) □	3 3/8" (86) □	2 5/8" (67) □	3 3/4" (95) □	3 3/4" (95) □
		5" (127) ○	3" (76) □	--	2 5/8" (67) □	3 3/4" (95) □	--
		6" (152) ○	3 1/4" (83) □	6 1/2" (165) □	--	--	--

SUFFIX OPTIONAL VARIATIONS

☐ -1	Nickel bronze strainer (standard)
☐ -3	Stainless steel strainer
☐ -5	Sediment bucket
☐ -6	Security screws (T-20 Torx & pin)
☐ -7	1/2" trap seal primer connection
☐ -8	Backwater valve (2", 3", 4")
☐ -11	Acid resistant epoxy coated body
☐ -13	Galvanized body
☐ -15	Extension
☐ -21	Secondary flat stainless steel strainer (2", 3", 4")
☐ -28	Stainless steel body (Type 304)
☐ -30	PVC socket connection body
☐ -31	ABS socket connection body
☐ -34	Closure plug

SUFFIX OPTIONAL VARIATIONS

☐ -40	Underdeck clamp
☐ -41	Sump receiver
☐ -49	Chrome plated strainer
☐ -90	Threaded side outlet (2", 3", 4") (cast iron only)
☐ -90NH	No hub side outlet (2", 3", 4") (cast iron only)
☐ -95	Client logo
☐ -BA	Buy American Act compliant product
☐ -C2	High rough-in membrane clamp (min. 1 9/16" (40)
☐ (Standard)	No hub outlet
☐ -MG	MI-GARD Floor Drain Trap Sealer (2", 3" or 4")
☐ P	Push on outlet
☐ -PA	Pennsylvania Steel Act compliant product
☐ T	Threaded outlet (2", 3", 4")
☐ X	Inside caulk outlet
☐ -Z	Extended wide elastomeric flange

CALIFORNIA PROPOSITION 65 WARNING. This product contains chemicals known to the State of California to cause cancer and birth defects or other reproductive harm.

Job Name: _____

Page No: _____

Section No: _____

Contractor: _____

Schedule No: _____

Purchase Order No: _____