


Location: **F1100-EG**

OVAL FUNNEL FLOOR DRAIN FOR NON-MEMBRANE FLOOR AREAS

Specification: MIFAB Series F1100-EG lacquered cast iron floor drain with anchor flange, weepholes, and standard 4" (102) x 9" (235) (specify strainer finish) open throat funnel with vandal resistant, stainless steel allen key screws. (For membrane floors, use MIFAB F1100-C-EG Series.)

Function: Used in restaurants, hospitals, industrial laboratories, and other non-membrane finished areas where indirect waste lines above the floor drip condensate or waste water into the hub. The funnel prevents splashing and directs the waste into the drain. The exposed section of the grate will drain any other water on the floor. The funnel is bolted to the grate with a concealed screw and may be moved to any other grate location. The 4" x 9" round funnel is recommended for multiple pipe use.



PARTS:



A1 BODY



EG(*)

(*) Denotes Strainer Finish (-1, -3 or 50)

F1100-EG Series meets
ANSI-ASME floor
drain standard
A112.6.3-2001

STRAINER DIAMETER	STRAINER ADJUSTMENT		PIPE SIZE	BODY HEIGHT				
	MIN	MAX		NO HUB (STANDARD)	PUSH ON (P)	THREADED (T)	INSIDE CAULK (X)	PVC/ABS (-30)/(-31)
5" (127) ●	1/2" (13)	1 1/2" (38)	2" (51) ●	3" (76) ☐	3 3/8" (86) ☐	2 1/4" (57) ☐	3 3/4" (95) ☐	2 15/16" (75) ☐
			3" (76) ●	3" (76) ☐	3 3/8" (86) ☐	2 5/8" (67) ☐	3 3/4" (95) ☐	3 3/4" (95) ☐
			4" (102) ●	3" (76) ☐	3 3/8" (86) ☐	2 5/8" (67) ☐	3 3/4" (95) ☐	3 3/4" (95) ☐
			5" (127) ●	3" (76) ☐	-- ☐	2 5/8" (67) ☐	3 3/4" (95) ☐	-- ☐
			6" (152) ●	3 1/4" (83) ☐	6 1/2" (165) ☐	-- ☐	-- ☐	-- ☐

SUFFIX OPTIONAL VARIATIONS

- ☐ -1 Nickel bronze strainer and funnel (standard)
- ☐ -3 Stainless steel strainer and funnel
- ☐ -5 Sediment bucket
- ☐ -6 Security screws (T-20 Torx & pin)
- ☐ -7 1/2" trap seal primer connection
- ☐ -8 Backwater valve (2", 3", 4")
- ☐ -11 Acid resistant epoxy coated body
- ☐ -13 Galvanized body
- ☐ -15 Extension
- ☐ -21 Secondary flat stainless steel strainer (2", 3", 4")
- ☐ -28 Stainless steel body (Type 304)

SUFFIX OPTIONAL VARIATIONS

- ☐ -30 PVC socket connection body
- ☐ -31 ABS socket connection body
- ☐ -34 Closure plug
- ☐ -40 Underdeck clamp
- ☐ -41 Sump receiver
- ☐ -49 Chrome plated strainer
- ☐ -50 Lacquered cast iron funnel for unfinished areas
- ☐ -90 Threaded side outlet (2", 3", 4") (cast iron only)
- ☐ -90NH No hub side outlet (2", 3", 4") (cast iron only)
- ☐ -95 Client logo

SUFFIX OPTIONAL VARIATIONS

- ☐ -BA Buy American Act compliant product
- ☐ -C Membrane clamp for low rough-in (min. 1/2" (13))
- ☐ -C2 High rough-in membrane clamp (min. 1 9/16" (40))
- ☐ (Standard) No hub outlet
- ☐ P Push on outlet
- ☐ -PA Pennsylvania Steel Act compliant product
- ☐ T Threaded outlet (2", 3", 4")
- ☐ X Inside caulk outlet
- ☐ -Z Extended wide elastomeric flange

Job Name:

Section No:

Schedule No:

Page No:

Contract:

Purchase Order No: