

Location: _____




F1650

**FLUSHING RIM FLOOR DRAIN
WITH FLUSHING CONNECTION**

Specification: MIFAB® Series F1650 flushing rim floor drain with white epoxy coated interior and exterior cast iron body, 3/4" (19) N.P.T. flushing connection, anchor flange, membrane clamp, and stain finished (specify material finish) grate and frame with stainless steel allen key vandal proof screws.

Function: Used in hospital operating and veterinary rooms, industrial and educational laboratories where waste must be drained to the sewer. Appropriate for mental institutions, zoos and prisons as drain type water closets.



Note: See F1670 for water supply control box to be used with the flushing rim floor drain Use a vacuum breaker between the potable water supply and the connection to the flushing rim connection (by others).

STRAINER DIAMETER	ANSI/ASME RATING			PIPE SIZE	BODY HEIGHT							
	FREE AREA	LOAD RATING			NO HUB (STANDARD)	PUSH ON (P)	THREADED (T)	INSIDE CAULK (X)	PVC/ABS (-30)/(-31)			
		N.B. (-1)	S.S. (-3)									
9" (229)	18 in² (11,613²)	UP TO 2,000 LBS.	2,000 TO 4,999 LBS.	2" (51) ○	6" (152) ☐	6 1/8" (156) ☐	5 7/16" (138) ☐	6 1/4" (159) ☐	7 1/8" (181) ☐			
				3" (76) ○	6" (152) ☐	6 1/8" (156) ☐	5 7/16" (138) ☐	6 1/4" (159) ☐	7 3/8" (187) ☐			
				4" (102) ○	6" (152) ☐	6 1/8" (156) ☐	5 7/16" (138) ☐	6 1/4" (159) ☐	7 3/8" (187) ☐			
				5" (127) ○	6" (152) ☐	— ☐	5 7/16" (138) ☐	6 1/4" (159) ☐	— ☐			
				6" (152) ○	7 1/4" (184) ☐	7" (178) ☐	7" (178) ☐	6 1/4" (159) ☐	— ☐			

SUFFIX OPTIONAL VARIATIONS

- ☐ -1 Nickel bronze frame and grate
- ☐ -3 Stainless steel frame and grate
- ☐ -5 Sediment bucket
- ☐ -6 Security screws (T-20 Torx & pin)
- ☐ -13 Galvanized body
- ☐ -21 Secondary flat stainless steel strainer (2", 3", 4")
- ☐ -25-1 Nickel bronze hinged solid cover
- ☐ -28 Stainless steel body (Type 304)
- ☐ -30 PVC socket connection body
- ☐ -31 ABS socket connection body
- ☐ -34 Closure plug
- ☐ -40 Underdeck clamp
- ☐ -41 Sump receiver

SUFFIX OPTIONAL VARIATIONS

- ☐ -90 Threaded side outlet (2", 3", 4")
- ☐ -90NH No hub side outlet (2", 3", 4")
- ☐ -95 Client logo
- ☐ -BA Buy American Act compliant product
- ☐ -HP Heel proof grate (1/4" maximum grate opening size, -3 only)
- ☐ (Standard) No hub outlet
- ☐ -MG MI-GARD Floor Drain Trap Sealer (2", 3" or 4")
- ☐ P Push on outlet
- ☐ -PA Pennsylvania Steel Act compliant product
- ☐ T Threaded outlet (2", 3", 4")
- ☐ X Inside caulk outlet
- ☐ -Z Extended wide elastomeric flange

Job Name: _____

Page No: _____

Section No: _____

Contractor: _____

Schedule No: _____

Purchase Order No: _____