

Location: _____




FS1530-FL

**8" X 4" X 4" FLOOR AREA AND INDIRECT
SANITARY WASTE DRAIN WITH FLANGE**

Specification: MIFAB Series FS1530-FL, 8" x 4" x 4" deep cast iron floor area and indirect sanitary waste drain complete with white acid resistant porcelain enamel coated interior and loose set grate and anchor flange with weepholes. Anti-splash aluminum dome strainer included.

Function: Used in kitchens, restaurants, grocery stores, hospitals, schools, and other areas that require a small volume sanitary drain. The anchor flange is engineered to receive water proofing membrane. Membrane clamps are recommended for use with the anchor flange (Suffix -C). Regular top is recommended for installation under counters and along walls. The light duty grate is not suitable for foot traffic.



PIPE SIZE	BODY HEIGHT				
	NO HUB (STANDARD)	PUSH ON (P)	THREADED (T)	INSIDE CAULK (X)	PVC/ABS (-30)/(-31)
2" (51)	*6 1/2" (165)	*7 1/4" (184)	*6 1/2" (165)	*8" (203)	*7 1/4" (184)
3" (76)	*6 1/2" (165)	*7 1/4" (184)	*6 7/8" (175)	*8" (203)	*7 1/4" (184)
4" (102)	*6 1/2" (165)	*7 1/4" (184)	*6 7/8" (175)	*8" (203)	*7 1/4" (184)

*Indicates outlet size and connection available with transition outlet body only

Outlet sizes indicated by the * are available with the transition outlet body only

SUFFIX OPTIONAL VARIATIONS

-1	Nickel bronze frame and grate
-3	Stainless steel frame and grate
-5	Sediment bucket
-6	Security screws (1, -3 only, H-1039A, 4 pcs.)
-7	1/2" trap seal primer connection
-8	Backwater valve (2", 3" or 4")
-21	Secondary flat stainless steel strainer
-22	Less grate
-30	PVC outlet
-31	ABS outlet
-32	Deep seal trap with flushing connection
-50	A.R.E. coated cast iron funnel
-51	2 1/2" round center hole in grate (-1, -3 only)
-69	Stainless steel sediment bucket
-83	Stainless steel mesh screen over sediment bucket
-90	Threaded side outlet

SUFFIX OPTIONAL VARIATIONS

-90NH	No hub side outlet
-95	Client logo (-1, -3 only)
-150	1/2" PVC grate
-175	3/4" PVC grate
-BA	Buy American Act compliant product
(Standard)	No hub outlet
-C	Membrane clamp with hardware
-F4	4" round funnel
-F6	6" round funnel
-G	4" x 9" oval funnel
-J	3" x 1" oval funnel
-P	Push on outlet
-PA	Pennsylvania Steel Act compliant product
-T	Threaded outlet
X	Inside caulk outlet
-Z	Extended wide elastomeric flange (with -FL only)

CALIFORNIA PROPOSITION 65 WARNING. This product contains chemicals known to the State of California to cause cancer and birth defects or other reproductive harm.

Job Name: _____

Page No: _____

Section No: _____

Contractor: _____

Schedule No: _____

Purchase Order No: _____