

Location: _____



FS1730-FL

**12" X 12" X 8" FLOOR AREA AND INDIRECT
SANITARY WASTE DRAIN WITH FLANGE**

Specification: MIFAB Series FS1730-FL, 12" x 12" x 8" deep cast iron floor area and indirect sanitary waste drain complete with white acid resistant porcelain enamel coated interior, loose set grate and anchor flange with weepholes. Anti-splash aluminum dome strainer included.

Function: Used in kitchens, restaurants, grocery stores, hospitals, schools, and other areas that require a large volume sanitary drain. Also suitable for indirect waste applications. The anchor flange is engineered to receive water proofing membrane. Membrane clamps are recommended for use with the anchor flange (Suffix -C). The light duty grate is not recommended for foot traffic.

FULL GRATE IS STANDARD.
½ GRATE (SUFFIX -150)
IS ILLUSTRATED

WEEPHOLES
WHITE ACID
RESISTANT
ENAMEL (A.R.E.)
COATED CAST
IRON BODY

(STANDARD) ALUMINUM
DOME STRAINER

10 ½"

A.R.E. LOOSE SET
GRATE

ANCHOR FLANGE
(14 ½" x 14 ½" O.D.)

8"
SEE BODY
HEIGHT
CHART

PIPE SIZE
(SEE CHART)

Add ½" to length and width and 3/8" to height for NB, SS frame and grate.

PIPE SIZE	BODY HEIGHT				
	NO HUB (STANDARD)	PUSH ON (P)	THREADED (T)	INSIDE CAULK (X)	PVC (-30) / ABS (-31)
2" (51)	9 3/4" (248)	9 3/4" (248)	*10 1/2" (267)	*12" (305)	*11 1/4" (286)
3" (76)	9 3/4" (248)	9 3/4" (248)	*10 7/8" (276)	10 5/8" (270)	*11 1/4" (286)
4" (102)	9 3/4" (248)	9 3/4" (248)	*10 7/8" (276)	10 5/8" (270)	*11 1/4" (286)

*Indicates outlet size and connection available with transition outlet body only.
Outlet sizes indicated by the * are available with the transition outlet body only

SUFFIX OPTIONAL VARIATIONS

-1 Nickel bronze frame and grate
-3 Stainless steel frame and grate
-5 Sediment bucket
-6 Security screws (1, -3 only, T-20 Torx and pin)
-7 ½" trap seal primer connection
-8 Backwater valve (2", 3" or 4")
-9 Hinged grate (-3 only)
-21 Secondary flat stainless steel strainer
-22 Less grate
see FS1930-FL Stainless steel body (Type 304)
see FS1930-FL Stainless steel body (Type 316)
-30 PVC outlet
-31 ABS outlet
-32 Deep seal trap with flushing connection
-50 A.R.E. coated cast iron funnel
-51 2 ½" round center hole in grate (-1, -3 only)
-69 Stainless steel sediment bucket
-83 Stainless steel mesh screen over sediment bucket

SUFFIX OPTIONAL VARIATIONS

-90 Threaded side outlet
-90NH No hub side outlet
-95 Client logo (-1, -3 only)
-150 1/2" PVC grate
-175 3/4" PVC grate
-BA Buy American Act compliant product
(Standard) No hub outlet
-F4 4" round funnel
-F6 6" round funnel
-FL Anchor flange
-G 4" x 9" oval funnel
-J 3" x 1" oval funnel
-P Push on outlet
-PA Pennsylvania Steel Act compliant product
-T Threaded outlet
X Inside caulk outlet
-Z Extended wide elastomeric flange (with -FL only)

CALIFORNIA PROPOSITION 65 WARNING. This product contains chemicals known to the State of California to cause cancer and birth defects or other reproductive harm.

Job Name: _____

Page No: _____

Section No: _____

Contractor: _____

Schedule No: _____

Purchase Order No: _____